

# DATENBLATT

## KM651 KELOX FB floor heating -Single Zone Control Unit





The Kelox floor heating single zone control unit regulates the temperature of individual floor heating loops. It works at the temperature level of radiator heating (e.g. 70/55°C)

The unit works on the principle of regulation by thermal injection and is installed directly to the manifold.

If all floor heating loops are closed automatically there must be a pump logic ( e.g the KM691 KELOX connection panel) which ensures that the pump switches off.

Ensure that there is hydraulic balance in the connecting pipelines.

Minimum depth required for the manifold box is 110mm


The components:

High efficiency Wilo pump – Yonos-Para 15/6, temperature monitor, thermostatic valve, thermostatic head, three-way valve and two female thread ball valves 3/4". All the components are connected to the manifold, ready for use .

The unit is compatible with all 1" KELOX floor heating manifolds. Extra width of 220mm is required.

#### Product data:

Code	KM651	Article number	7952000
Compatible with	KM590E, KMU590E, KMP590M, KMP590E	Zollnummer	84818039
Pump	Yonos-Para 15/6	<b>Operating Conditions</b>	tmax. 80°C/6bar
Temperature monitor	Pump switches off at 55°C +3K and switches back on at 52°C -4K; maximum ambient temperature 80°C; bridging time for pump after temperature controller is switched on: 5 minutes		





Kunststoffwerk Gesellschaft m.b.H. A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe PHONE +43 (0) 50 779 MAIL office@kekelit.com www.kekelit.com

Seite 1/2




180831

Ľ



## DATENBLATT

### KM651 KELOX FB floor heating -Single Zone Control Unit



Accessories		
Article number	Description	
7951020	KM650 Single Zone Control Unit pump	



Kunststoffwerk Gesellschaft m.b.H. A 4020 Linz, Ignaz-Mayer-Straße 17, Austria, Europe PHONE +43 (0) 50 779 MAIL office@kekelit.com www.kekelit.com



З