


Product Data Sheet

Meiflex - Reinforced hoses for heating / air-conditioning F x F

Meiflex reinforced hoses for heating / air-conditioning with stainless steel braid and EPDM inliner.

- Reinforced hoses with stainless steel braid for heating and air-conditioning systems with red identification.
- Internal hose made from EPDM (not impermeable), resistant against water and glycol-based antifreeze (max. 50%).



Type	Connection ["]	Length * [mm]	Internal Ø [mm]	Weight [kg]	###	Order Code
Meiflex SST $\frac{3}{8}$ F/F x 300	$\frac{3}{8}$ " F x $\frac{3}{8}$ " F	300	10	0,10	1	M4315.0201.30
Meiflex SST $\frac{3}{8}$ F/F x 500	$\frac{3}{8}$ " F x $\frac{3}{8}$ " F	500	10	0,14	1	M4315.0201.50
Meiflex SST $\frac{1}{2}$ F/F x 300	$\frac{1}{2}$ " F x $\frac{1}{2}$ " F	300	10	0,10	1	M4315.0204.30
Meiflex SST $\frac{1}{2}$ F/F x 500	$\frac{1}{2}$ " F x $\frac{1}{2}$ " F	500	10	0,14	1	M4315.0204.50
Meiflex SST $\frac{1}{2}$ F/F x 300	$\frac{1}{2}$ " F x $\frac{1}{2}$ " F	300	13	0,14	1	M4315.1204.30
Meiflex SST $\frac{1}{2}$ F/F x 500	$\frac{1}{2}$ " F x $\frac{1}{2}$ " F	500	13	0,20	1	M4315.1204.50
Meiflex SST $\frac{3}{4}$ F/F x 300	$\frac{3}{4}$ " F x $\frac{3}{4}$ " F	300	13	0,18	1	M4315.1207.30
Meiflex SST $\frac{3}{4}$ F/F x 500	$\frac{3}{4}$ " F x $\frac{3}{4}$ " F	500	13	0,22	1	M4315.1207.50
Meiflex SST $\frac{1}{2}$ F/F x 300	$\frac{1}{2}$ " F x $\frac{1}{2}$ " F	300	15	0,17	1	M4325.1221.30
Meiflex SST $\frac{1}{2}$ F/F x 500	$\frac{1}{2}$ " F x $\frac{1}{2}$ " F	500	15	0,24	1	M4325.1221.50
Meiflex SST $\frac{1}{2}$ F/F x 700	$\frac{1}{2}$ " F x $\frac{1}{2}$ " F	700	15	0,29	1	M4325.1221.70
Meiflex SST $\frac{1}{2}$ F/F x 1000	$\frac{1}{2}$ " F x $\frac{1}{2}$ " F	1000	15	0,38	1	M4325.1221.100
Meiflex SST $\frac{3}{4}$ F/F x 300	$\frac{3}{4}$ " F x $\frac{3}{4}$ " F	300	18	0,27	1	M4325.1227.30
Meiflex SST $\frac{3}{4}$ F/F x 500	$\frac{3}{4}$ " F x $\frac{3}{4}$ " F	500	18	0,35	1	M4325.1227.50
Meiflex SST $\frac{3}{4}$ F/F x 700	$\frac{3}{4}$ " F x $\frac{3}{4}$ " F	700	18	0,44	1	M4325.1227.70

Type	Connection ["]	Length * [mm]	Internal Ø [mm]	Weight [kg]	###	Order Code
Meiflex SST 3/4" F/F x 1000	3/4" F x 3/4" F	1000	18	0,58	1	M4325.1227.100
Meiflex SST 1" F/F x 300	1" F x 1" F	300	25	0,40	1	M4325.1234.30
Meiflex SST 1" F/F x 500	1" F x 1" F	500	25	0,50	1	M4325.1234.50
Meiflex SST 1" F/F x 700	1" F x 1" F	700	25	0,62	1	M4325.1234.70
Meiflex SST 1" F/F x 1000	1" F x 1" F	1000	25	0,90	1	M4325.1234.100
Meiflex SST 1 1/4" F/F x 300	1 1/4" F x 1 1/4" F	300	32	0,66	1	M4325.1242.30
Meiflex SST 1 1/4" F/F x 500	1 1/4" F x 1 1/4" F	500	32	0,84	1	M4325.1242.50
Meiflex SST 1 1/4" F/F x 700	1 1/4" F x 1 1/4" F	700	32	1,04	1	M4325.1242.70
Meiflex SST 1 1/4" F/F x 1000	1 1/4" F x 1 1/4" F	1000	32	1,32	1	M4325.1242.100
Meiflex SST 1 1/2" F/F x 500	1 1/2" F x 1 1/2" F	500	40		1	M4325.1248.50
Meiflex SST 2" F/F x 500	2" F x 2" F	500	50		1	M4325.1260.50

* Other lengths available upon request.

Advantages

- Flexible connections in certified quality.
- Prevents stresses and transmission of structure-borne noise.
- Numerous connection types.

Technical information

- For temperatures between -5 and +110 °C.
- Operating pressures:
16 bar (up to 100 °C, up to DN32).
10 bar (up to 110 °C, up to DN32).
6 bar (up to 110 °C, from DN40).
- Connections: Brass, copper elbows, with union nut and flat gasket.