

Product Data Sheet

BigFixlock F including insulation

Connection clamp with flange connection including insulation.

When used without boiler guard. When using the boiler guard, please select unions without insulation. Connections directly from the manifold to the heat generator (without boiler guard) should be selected without insulation.

- 1 pair (2 x).
- Further unions upon request.



Type	Ø pipe (V, HZW)*		Ø pipe (heat generator)* (flange connection) DN	###	Order Code
	DN	External dimension [mm]			
BigFixlock F DN 100 - DN 40	100	114.3	40	1	M66258.691
BigFixlock F DN 100 - DN 50	100	114.3	50	1	M66258.692
BigFixlock F DN 100 - DN 65	100	114.3	65	1	M66258.693
BigFixlock F DN 100 - DN 80	100	88.9	80	1	M66258.694
BigFixlock F DN 150 - DN 100	150	114.3	100	1	M66258.891
BigFixlock F DN 150 - DN 125	150	168.3	125	1	M66258.892
BigFixlock F DN 150 - DN 150	150	168.3	150	1	M66258.893
BigFixlock F DN 200 - DN 200	200	219.1	200	1	M66258.992

*HZW = Boiler guard / V = Manifold / WEZ = Heat generator

Advantages

The "BigFixLock quick-connection system is characterised by its quick and easy installation. During installation, the pipes are laid out end to end with a specially shaped sealing ring, and grey cast iron half-shells are placed around the pipes in such a way that they lie in the beading of the pipe ends. The half-shells secure both the pipe ends and the seal in place.