

## Product Data Sheet (2019-08-01)

### BigFixlock F

Connection clamp with flange connection.

- 1 pair (2 x).



Type	Ø pipe (V, HZW)*		Ø pipe (heat generator)* (flange connection) DN	###	Order Code
	DN	External dimension [mm]			
BigFixlock F DN 50 - DN 40	50	60.3	40	1	M66259.391
BigFixlock F DN 50 - DN 50	50	60.3	50	1	M66259.392
BigFixlock F DN 65 - DN 65	65	76.1	65	1	M66257.49
BigFixlock F DN 80 - DN 65	80	88.9	65	1	M66259.592
BigFixlock F DN 80 - DN 80	80	88.9	80	1	M66259.593
BigFixlock F DN 100 - DN 100	100	114.3	100	1	M66259.695
BigFixlock F DN 150 - DN 125	150	168.3	125	1	M66259.892
BigFixlock F DN 150 - DN 150	150	168.3	150	1	M66259.893
BigFixlock F DN 200 - DN 200	200	219.1	200	1	M66259.992

\*HZW = Boiler guard / V = Manifold / WEZ = Heat generator

### Advantages

The "BBigFixLock quick-connection system is characterised by its quick and easy installation. During installation, the pipes are laid out end to end with a specially shaped sealing ring, and grey cast iron half-shells are placed around the pipes in such a way that they lie in the beading of the pipe ends. The half-shells secure both the pipe ends and the seal in place.

**Find more information online:**

[Animations](#)