

Product Data Sheet

BigFixlock S including insulation

Connection clamp with welded connection, including insulation.

When used without boiler guard. When using the boiler guard, please select unions without insulation. Connections directly from the manifold to the heat generator (without boiler guard) should be selected without insulation.

- 1 pair (2 x).
- Further unions upon request.



Type	Ø pipe (V, HZW)*		Ø pipe (heat generator)* (welded connection)		###	Order Code
	DN	External dimension [mm]	DN	External dimension [mm]		
BigFixlock S DN 100 - DN 40	100	114.3	40	48,3	1	M66258.671
BigFixlock S DN 100 - DN 50	100	114.3	50	60,3	1	M66258.672
BigFixlock S DN 100 - DN 65	100	114.3	65	76,1	1	M66258.673
BigFixlock S DN 100 - DN 80	100	114.3	80	88,9	1	M66258.674
BigFixlock S DN 150 - DN 100	150	168.3	100	114,3	1	M66258.871
BigFixlock S DN 150 - DN 125	150	168.3	125	141,3	1	M66258.872
BigFixlock S DN 150 - DN 150	150	168.3	150	168,3	1	M66258.873
BigFixlock S DN 200 - DN 200	200	219.1	200	219,1	1	M66258.972

*HZW = Boiler guard / V = Manifold / WEZ = Heat generator

Advantages

The "BBigFixLock quick-connection system is characterised by its quick and easy installation. During installation, the pipes are laid out end to end with a specially shaped sealing ring, and grey cast iron half-shells are placed around the pipes in such a way that they lie in the beading of the pipe ends. The half-shells secure both the pipe ends and the seal in place.