

## Product Data Sheet

### Constant heat regulation set ed. 8

With electronically controlled actuator.

The constant heat regulation set is designed for a mixed heating circuit with constant flow line temperature, with a mixer for underfloor heating. The supply temperature is adjusted using the 3-way T-mixer. The adjustable bypass is used to mix water from the return line into the flow line. The contact thermostat included in delivery is a safety temperature monitor (STW).

Recirculation pump (installed length 180 mm) with connection cable, two ball valves (with manually adjustable backflow limiter in the return line), two contact thermometers, 3-way T-mixer with adjustable bypass, contact thermostat, wall bracket, return line pipe with actuator (230V~, 50 Hz) with integrated temperature controller (adjustment range 0 °C - 95 °C); flow line temperature sensor in flow line ball valve, EPP insulation, all fully assembled.



Type	Model	Connection (uppermost)		###	Order Code
		DN	"		
Constant heat regulation set DN 25	Without pump	25	1"	1	M45890.5EA
Constant heat regulation set DN 25	Without pump	25	1"	1	M45890.5EA
Constant heat regulation set DN 25	With Grundfos UPM3 Hybrid 25-70*	25	1"	1	M45890.56
Constant heat regulation set DN 25	With Grundfos Alpha2.1 25-60	25	1"	1	M45890.50
Constant heat regulation set DN 25	With Wilo Yonos PICO 25/1-6	25	1"	1	M45890.5WI
Constant heat regulation set DN 25	With Wilo Stratos PICO 25/6	25	1"	1	M45890.52WI

\* Optional PWM signal cable and suitable heat flow meter available.