

Product Data Sheet

CB Clips - 19 mm

For mounting pipework with an elastomer insulation to the wall or ceiling to prevent thermal losses.



Type	Ø pipe		Max. vertical working load [N]	Strip dimensions [mm]	Dimensions					###	Order Code
	Ext. dia. [mm]	Nom. ["]			A [mm]	B [mm]	C [mm]	D [mm]	E [mm]		
CB 19 x 18	18		70	20 x 1.5	98	32	15	64	19	10	39886
CB 19 x 22 - 1 1/2	22	1 1/2	80	20 x 1.5	98	32	15	64	19	10	39887
CB 19 x 28 - 3/4	28	3/4	100	20 x 1.5	104	35	15	70	19	10	39888
CB 19 x 35 - 1	35	1	130	20 x 1.5	115	40	15	80	19	10	39889
CB 19 x 42 - 1 1/4	42	1 1/4	160	20 x 2.0	122	43	15	86	19	10	39890
CB 19 x 48-50 - 1 1/2	50	1 1/2	190	20 x 2.0	128	46	15	92	19	10	39891
CB 19 x 54	54	-	210	20 x 2.0	134	49	15	98	19	10	39897
CB 19 x 60 - 2	60	2	230	20 x 2.0	140	52	15	104	19	10	39892
CB 19 x 64	64	-	240	20 x 2.0	140	52	15	104	20	10	39898
CB 19 x 76 - 2 1/2	76	2 1/2	290	20 x 2.5	155	60	15	120	20	10	39893
CB 19 x 89-90 - 3	90	3	850	20 x 2.5	177	70	15	140	24	10	39894
CB 19 x 114 - 4	114	4	1100	20 x 2.5	211	87	15	174	26	10	39895

Advantages

- Easy to bond with pipework insulation. No thermal bridge.
- All clips are fitted with two cross head screws.
- Clips fitted with quick-locking system and bolts designed not to fall out during installation: all sizes except 114-4".
- Clips fitted with retaining ring: CB 13 x 114-4" and CB 19 x 114-4".

Technical information

- Clip: electrolytically zinc plated.
- Insulation: 19 Elastomeric foam with a PIR core and coated with a black PVC foil.
- Connection: M 8/10.
- Insulation width: 50 mm.
- PIR density 80 kg/m³, PIR pressure resistance 0,52 N/mm²: CB 13 x 15 up to CB 13 x 60-2" and CB 19 x 18 up to CB 19 x 76-2½".
- PIR density 120 kg/m³, PIR pressure resistance 1,3 N/mm²: other sizes.
- Suitable for temperatures from -50 °C up to +110 °C.
- Thermal conductivity: maximal 0.033 W/(m.K).
- Vapour permeability: 10000 µ.
- Fire rating B2 according to DIN 4102/1.
- Fire rating B1 according to 4102/1 as part of a system with tubes, elastomer insulation.



Find more information online:

[Extra documentation](#)



KE KELIT NZ Ltd.
0800 4 KE KELIT
0800 4 5353548
info@kekelit.co.nz
www.kekelit.co.nz