

REMS Mini-Press ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. For battery and corded operation.

Pipe pressing joints $\varnothing$ 10–40 mm 7 $\varnothing$ $\frac{3}{8}$ –1 $\frac{1}{4}$

Complete range of REMS pressing tongs Mini/pressing rings for all common pressfitting systems, see page 144–166.

REMS Mini-Press ACC – universal up to $\varnothing$ 40 mm. Super light, super small, super handy. With automatic circuit control. Secure crimping in seconds. Automatic locking of the pressing tongs.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 144–166). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS 45° (PR-2B) pressing rings, see page 166.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

Design

Super light, super small, super handy. Drive unit with battery only 2.4 kg. Drive unit with pressing tongs V22 only 33 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Ergonomically designed housing. LED work light for illuminating the work place. Swivelling pressing tongs seat. Secure seating of pressing tongs/adapter tongs by automatic locking. Electronic charging status check with flat battery protection and charging status indicator with 2-coloured LED.

Pressing operation by touch-control with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control).

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 14.4 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion PLUS technology. Highly resistant Li-Ion 14.4 V battery with 1.5 or 3.0 Ah capacity for long service life. Light and powerful. Li-Ion 14.4 V, 3.0 Ah battery for approx. 330 pressings Viega Profipress DN 15 with one battery charge. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. Rapid charger 220–240 V, 10.8–18 V, 65 W, for short charging times. 220–240 V/14.4 V, 33 A, voltage supply for mains operation instead of Li-Ion battery 14.4 V, as accessory.

Supply format

REMS Mini-Press ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints $\varnothing$ 10–40 mm, $\varnothing$ $\frac{3}{8}$ –1 $\frac{1}{4}$ ". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 14.4 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, Safety tip switch. LED work light. Battery Li-Ion 14.4 V, 1.5 Ah, rapid charger Li-Ion/Ni-Cd 220–240 V, 50–60 Hz, 10.8–18 V, 65 W.

Version	Art.-No.
In sturdy steel case.	578012
In L-Boxx system case.	578013

Other voltages on request.

Accessories

Description	Art.-No.
REMS pressing tongs Mini/pressing rings see page 144–166.	
REMS cropping tongs Mini for threaded rods see page 167.	
REMS Mini-Press ACC drive unit, without battery	578001
Battery Li-Ion 14.4 V, 1.5 Ah	571545
Battery Li-Ion 14.4 V, 3.0 Ah	571555
Rapid charger Li-Ion/Ni-Cd 220–240 V, 50–60 Hz, 10.8–18 V, 65 W	571560
Voltage supply 220–240 V/14.4 V, 50–60 Hz, 33 A, for mains operation instead of battery Li-Ion 14.4 V.	571565
Steel case with inlay	578290
L-Boxx system case with inserts	578299
REMS cordless LED lamp see page 105	175200



German Quality Product



Tested by electrosuisse



REMS Mini-Press 22V ACC

Cordless radial press 22 kN with automatic circuit control

Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22 V Technology. For battery and corded operation.

Pipe pressing joints $\varnothing 10-40 \text{ mm} / \varnothing \frac{3}{8}-1 \frac{1}{4}"$

Complete range of REMS pressing tongs Mini/pressing rings for all common pressfitting systems, see page 144–166.

REMS Mini-Press 22V ACC – universal up to $\varnothing 40 \text{ mm}$. Super light, super small, super handy, ultra fast. Pressing under 4 s. Automatic pressing process. With automatic circuit control. Li-Ion 21.6V, 1.5Ah battery for approx. 250 pressings Viega Profipress DN 15 with one battery charge.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 144–166). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS 45° (PR-2B) pressing rings, see page 166.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

Design

Super light, super small, super handy. Drive unit with battery only 2.5 kg. Drive unit with pressing tongs V 15 only 31 cm long. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle $>360^\circ$. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6V battery with 1.5, 2.5, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Li-Ion 21.6V, 1.5Ah batteries for approx. 250 pressings, 2.5Ah for approx. 390 pressings, 5.0Ah for approx. 780 pressings, 9.0Ah for approx. 1400 pressings Viega Profipress DN 15 with one battery charge. Graduated charging state display with coloured LED. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger Li-Ion 100–240 V, 90 W. Rapid charger Li-Ion 100–240 V, 290 W, for shorter charging times, as accessory. 220–240 V/21.6 V, 15A, voltage supply for mains operation instead of Li-Ion battery 21.6 V, as accessory.



German Quality Product



Tested by electrosuisse >>>



Info



Supply format

REMS Mini-Press 22V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10–40 mm, Ø ¾–1 ¼". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 1.5 Ah, rapid charger Li-Ion 220–240 V or 110 V, 50–60 Hz, 70 W.

Version	Art.-No.	
In sturdy steel case.	578010	
In L-Boxx system case.	578014	
Other voltages on request.		

Accessories

Description	Art.-No.	
REMS pressing tongs Mini/pressing rings see page 144–166.		
REMS cropping tongs Mini for threaded rods see page 167.		
REMS Mini-Press 22V ACC drive unit, without battery	578002	
Battery Li-Ion 21.6V, 1.5Ah	571570	
Battery Li-Ion 21.6V, 2.5Ah	571571	
Battery Li-Ion 21.6V, 5.0Ah	571581	
Battery Li-Ion 21.6V, 9.0Ah	571583	
Rapid charger Li-Ion 100–240 V, 50–60 Hz, 90 W	571585	
Rapid charger Li-Ion 100–240 V, 50–60 Hz, 290 W	571587	
Voltage supply 220–240 V/21.6 V, 50–60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567	
Steel case with inlay	578290	
L-Boxx system case with inserts	578299	



Universal, super handy electric tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems. Li-Ion 22V Technology. For battery and corded operation.

Pipe pressing joints $\varnothing$ 10–40 mm / $\varnothing$ $\frac{3}{8}$ –1 $\frac{1}{4}$ "

Complete range of REMS pressing tongs Mini/pressing rings for all common pressfitting systems, see page 144–166.

REMS Mini-Press S 22V ACC – universal up to $\varnothing$ 40 mm. Super light, super small, super handy, ultra fast. Pressing under 4 s. Automatic pressing process. With automatic circuit control. Li-Ion 21.6V, 1.5Ah battery for approx. 250 pressings Viega Profipress DN 15 with one battery charge.

Pressing tongs for all common systems

Complete assortment of REMS pressing tongs Mini/pressing rings for all common pressfitting systems (page 144–166). Can be driven by all REMS radial presses 22 kN. Highly durable pressing tongs/pressing rings made of forged, tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond to the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Adapter tongs required for driving the REMS 45° (PR-2B) pressing rings, see page 166.

Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

Design

Super light, super small, super handy. Drive unit with battery only 2.6 kg. Works anywhere, free-hand, overhead, also in particularly tight areas. Optimum weight distribution for single-hand operation. Drive unit with inserted pressing tongs can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Swivelling pressing tongs seat, rotation angle $>360^\circ$. Secure seating of pressing tongs/adapter tongs by automatic locking.

Pressing operation with ACC

For reliable service, operating and functional safety. Automatic retraction after completion of pressing operation (automatic circuit control). Ultra fast Pressing under 4 s.

Drive

Enormous thrust and pressing force for fast and perfect press jointing. Thrust force 22 kN. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6V battery with 1.5, 2.5, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Li-Ion 21.6V, 1.5Ah batteries for approx. 250 pressings, 2.5Ah for approx. 390 pressings, 5.0Ah for approx. 780 pressings, 9.0Ah for approx. 1400 pressings Viega Profipress DN 15 with one battery charge. Graduated charging state display with coloured LED. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger Li-Ion 100–240 V, 90 W. Rapid charger Li-Ion 100–240 V, 290 W, for shorter charging times, as accessory. 220–240 V/21.6 V, 15A, voltage supply for mains operation instead of Li-Ion battery 21.6 V, as accessory.



German Quality Product



Tested by electrosuisse >>>



Info

Supply format

REMS Mini-Press S 22V ACC Basic-Pack. Cordless radial press 22 kN with automatic circuit control for producing pipe pressing joints Ø 10–40 mm, Ø ¾–1 ¼". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 1.5 Ah, rapid charger Li-Ion 220–240 V or 110 V, 50–60 Hz, 70 W.

Version	Art.-No.	
In sturdy steel case.	578015	
In L-Boxx system case.	578016	

Other voltages on request.

Accessories

Description	Art.-No.	
REMS pressing tongs Mini/pressing rings see page 144–166.		
REMS cropping tongs Mini for threaded rods see page 167.		
REMS Mini-Press S 22V ACC drive unit, without battery	578003	
Battery Li-Ion 21.6 V, 1.5 Ah	571570	
Battery Li-Ion 21.6 V, 2.5 Ah	571571	
Battery Li-Ion 21.6 V, 5.0 Ah	571581	
Battery Li-Ion 21.6 V, 9.0 Ah	571583	
Rapid charger Li-Ion 100–240 V, 50–60 Hz, 90 W	571585	
Rapid charger Li-Ion 100–240 V, 50–60 Hz, 290 W	571587	
Voltage supply 220–240 V/21.6 V, 50–60 Hz, 15 A, for mains operation instead of battery Li-Ion 21.6 V.	571567	
Steel case with inlay	578290	
L-Boxx system case with inserts	578299	



for all common pressfitting systems

Select REMS pressing tongs Mini/ REMS pressing rings yourself!

Find the desired press fitting system in the table below and choose the size of pressing tongs/pressing rings that you require. Please note that pressfitting systems for gas installation may only be pressed with the REMS pressing tongs Mini/pressing rings which are highlighted in yellow in the table.

Highly durable pressing tongs/pressing rings made of tenacious, specially hardened special steel. Pressing contours of REMS pressing tongs/pressing rings are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing. Pressing jaws of pressing tongs/pressing rings manufactured on CNC production centres ensure high-precision machining of pressing contour. Low production tolerances as a result.

Can be driven by all REMS radial presses 22 kN. Adapter tongs (page 166) required for driving REMS (PR) pressing rings. Read and observe the instructions for use and assembly instructions of the system provider/manufacturer.

REMS pressing tongs Mini (PZ-2B)

REMS Mini pressing tongs (PZ-2B) with 2 swivellable monoblock pressing jaws. Very compact design and low weight of the REMS Mini pressing tongs due to special arrangement of the pressing tongs connection (**Patent EP 1 952 948**). Recesses in the pressing jaws for safe guidance of the connecting plate for offset-free pressing (**Patent EP 2 347 862**).

REMS Mini ACz, Fz, HEz, RFz, RFlz pressing tongs with teeth prevent formation of burr on the pressfitting (**Patent EP 2 027 971**).

REMS pressing ring 45° (PR-2B)

REMS pressing ring 45° (PR-2B), with 2 pressing jaws, for secure engagement of the pressing jaws in places of difficult access by 45° inclination (**Patent EP 2 774 725**). Adapter tongs required for driving the REMS 45° (PR-2B) pressing rings, see page 166.

Traceability according to EN 1775:2007

REMS pressing tongs Mini with pressing contour F, M, V, SA, B, RN and UP have worked a specific marking into the pressing contour which leaves a lasting impression on the pressed fitting after the pressing process. This enables the user to check again whether the most suitable pressing tongs have been used to make the pressfit connection even after the pressing process.

With this traceability REMS fulfils the recommendations of the European standard EN 1775:2007 for the installation of pressfitting systems for gas.



German Quality Product



REMS Mini pressing tongs (PZ-2B)



REMS pressing ring 45° (PR-2B)
Patent EP 2 774 725


Confirmation of suitability

See page 213.


Hold-Harmless and Indemnification Agreement

See page 214.





Pressing tongs with teeth prevent formation of burr on the pressfitting.
 Patent EP 2 027 971



Example REMS pressing tongs Mini V:
 "V" imprint on pressed fitting for
 traceability according to EN 1775:2007

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
A			
AC-FIX PRESS (Global Piping Systems)	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	H 32		578412
	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	VX 16		578552
	VX 20		578554
AC-FIX PRESS DUO (Global Piping Systems)	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 25		578380
AC-FIX PRESS-MULTI (Global Piping Systems)	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 32		578412
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	U 16		578374
	U 18		578376
	U 20		578378
ACOME ACOPEX ALU	U 25		578380
	U 32		578382
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
ACOME MT	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 32		578382
	ACz 12		578608
AHLSELL A-press elförzinkad M	ACz 16		578610
	ACz 20		578612
	ACz 25		578614
	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
AHLSELL A-press elförzinkad V	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
AHLSELL A-press koppar M	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578318
	M 35		578390
AHLSELL A-press koppar V	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
AHLSELL A-press rostfritt	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
AIRBEL PRESSCLIM	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
AIRBEL SERTINOX	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
ALB Sistema Multicapa	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 18		578376
	U 20		578378
ALB Sistema Multicapa Gas	C 26		578392
	U 32		578382
	U 40		578386
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	H 16		578400
ALTECH Altech	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
	RFz 12		578490
APE MULTYGAS Serie AP Gas	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	TH 16		578352
	TH 20		578358
APE Serie AP	TH 26		578362
	TH 32		578364
	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
APE Serie APL	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 18		578376
	U 20		578378
	U 40		578386
	H 16		578400
AQUATECHNIK Press-fitting metal	H 18		578404
	H 20		578406
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 32		578364
	U 16		578374
	U 20		578378
	U 32		578382
	H 16		578400
AQUATECHNIK Universal	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	C 26		578392

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
ARKA DUROsystem	H 16		578400
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
Aschl NIR	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
ASSOTHERM IPC-RAC Carbon Steel	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
ASSOTHERM IPI-RAX Inox	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
ASSOTHERM IPI-RAX Inox Gas	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
ASSOTHERM IPM-Multistrato	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	THL 32		578368
	TH 40		578624
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
ASSOTHERM IPR-RRA Copper	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
ASSOTHERM IPR-RRA Copper Gas	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
ASTM F 1807 (Fittings with Copper Crimp Ring for PEX tubing)	US ¾"		578534
	US ½"		578536
	US ¾"		578538
	US 1"		578540
AYOR FIXOCONNECT Press	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	U 16		578374
	U 20		578378
	U 25		578380

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
AYOR FIXOMULTIX	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 32		578382
	U 40		578386
AYOR SOMATHERM FOR YOU -1	H 16		578400
	H 20		578406
	H 26		578410
	TH 16		578352
	TH 20		578358
	TH 26		578362
	U 16		578374
AYOR SOMATHERM FOR YOU -2	U 20		578378
	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	U 16		578374
	U 20		578378
	U 25		578380
B			
Bampi BALPEX serie LP	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
Bampi BALPEX serie MP	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
Bampi BALPEX Gas	TH 40		578624
	TH 16		578352
	TH 20		578358
	TH 26		578362
BARBI EASYPRESS (Industrial Blansol)	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	H 32		578412
	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
BARBI MULTIPLEX (Industrial Blansol)	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	RFz 16		578492
	RFz 18		578638
	RFz 20		578494
BEGETUBE/IVAR	RFz 25		578496
	RFz 32		578498
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	B 14		578466
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For taking suitable pressing inserts.
- Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website: www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Béné inox Série 41	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
BRASELI GPF GAS	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
BRASELI Pressfitting PE-X	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
BRASELI Pressfitting Multicapa	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
Brass Form Master Press	H 16		578400
	H 18		578404
	H 20		578406
	TH 16		578352
	TH 18		578356
	TH 20		578358
	U 16		578374
	U 18		578376
	U 20		578378
Brass & Fittings PRESSMAN MultiPress	RFz 16		578492
	RFz 18		578638
	ACz 20		578612
	RFz 25		578496
	RFz 32		578498
Brass & Fittings PRESSMAN RetiPress	RFz 16		578492
	RFz 18		578638
	ACz 20		578612
	RFz 25		578496
	RFz 32		578498
BRASSTECH MULTitermoSAN Brasspress	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	F 26		578462
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 16		578374
	U 18		578376
	U 20		578378
	C 26		578392
	U 32		578382
C			
Cello Products Press	VUS ½" (OD 15,9mm)		578566
	VUS ¾" (OD 22,2mm)		578568
	VUS 1" (OD 28,6mm)		578570
	VUS 1¼" (OD 34,9mm)		578606
CGR DYNAFLU multicouche	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 32		578382
	U 40		578386
CGR DYNAFLU PER	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	RFz 12		578490
CHIALI CHIALIPEX	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	TH 16		578352
	TH 20		578358
Climatek Clima Therm	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 14		578348
	TH 16		578352
Climatrix Climatrix Rhinopex	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	H 16		578400
	H 20		578406
	U 16		578374
	U 20		578378
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
ClouSet	TH 16		578352
	TH 18		578356
	TH 20		578358
Comap PEX Press	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
Comap Multiskin	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	THL 32		578368
	TH 40		578624
	U 16		578374
	U 20		578378
Comap Multiskin Gas	U 32		578382
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	THL 32		578368
COMISA Press System	U 16		578374
	U 20		578378
	U 32		578382
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	H 14		578398
	H 16		578400
	H 18		578404
COMISA Press System Gas	H 20		578406
	H 26		578410
	H 32		578412
	B 14		578466
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476
	TH 16		578352
CONEL CONNECT MULTI	TH 20		578358
	TH 26		578362
	TH 32		578364
	F 16		578456
	F 20		578460
	F 26		578462
(DN 26)	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	VP 16		578482
CONEL CONNECT MV2	VP 20		578484
	VP 32		578488
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	TH 16		578352
	TH 20		578358
Conex Bänninger >B< Flex	TH 26		578362
	TH 32		578364
	F 16		578456
	F 18		578458
	F 20		578460
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 32		578412
	RFz 16		578492
	RFz 18		578638
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 32		578364
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Conex Bänninger >B< MaxiPro	BMP ½"		578700
	BMP ¾"		578702
	BMP 1"		578704
	BMP 1 ¼"		578706
	BMP 1 ½"		578708
	BMP 1 ¾"		578710
	BMP 2"		578712
Conex Bänninger >B< Press	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 14 45° (PR-2B)	Mini Z1	574532
	V 15 45° (PR-2B)	Mini Z1	574504
	V 16 45° (PR-2B)	Mini Z1	574534
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
Conex Bänninger >B< Press Carbon	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
Conex Bänninger >B< Press Gas	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 14 45° (PR-2B)	Mini Z1	574532
	V 15 45° (PR-2B)	Mini Z1	574504
	V 16 45° (PR-2B)	Mini Z1	574534
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
Conex Bänninger >B< Press Inox	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
Conex Bänninger >B< Press Solar	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 14 45° (PR-2B)	Mini Z1	574532
	V 15 45° (PR-2B)	Mini Z1	574504
	V 16 45° (PR-2B)	Mini Z1	574534
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
Debrunner Acifer d-a Presssystem C-Stahl	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
DIWAsystems	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624

D

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
DUOFIL MKSYSYSTEM	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
DW Verbundrohr multitubo systems	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
E			
EBRILLE Isomontflex	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	H 26		578410
	TH 26		578362
	U 32		578382
EBRILLE Montflex	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	H 26		578410
	TH 26		578362
EFFEBI PRESSTIGE	U 32		578382
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
EFFEBI TOF-GAS MULTIPINZA	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
EFFEBI TOF MULTIPINZA	U 20		578378
	U 32		578382
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	F 16		578456
	F 18		578458
	F 20		578460
	F 26		578462
	F 32		578464
	Fz 40		578478
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
EFIELD MULTILAYER PRESS DINGAS	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	C 26		578392
	U 32		578382
	U 40		578386
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476
EFIELD MULTILAYER PRESS DINGAS	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
 - For taking suitable pressing inserts.
 - Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.
- The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website: www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.
- See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
EFIELD MULTILAYER PRESS WATER	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
Elkhart APOLLOXPRESS Fittings Copper and Low-Lead Brass	VUS ½" (OD 15,9 mm)		578566
	VUS ¾" (OD 22,2 mm)		578568
	VUS 1" (OD 28,6 mm)		578570
	VUS 1¼" (OD 34,9 mm)		578606
EMMETT GERPEX- FIVPRESS	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	H 16		578400
	H 20		578406
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 16		578374
	U 20		578378
EMPUR	TH 14		578348
	TH 15		578350
	TH 16		578352
	TH 17		578354
	TH 20		578358
EURACCORDI SYCPRESS STAINLESS STEEL PRESS FITTINGS	TH 25		578360
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
EURACCORDI SYCPRESS CARBON STEEL PRESS FITTINGS	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
EUROTUBI EUROPA C-Steel Pressfitting System M-Profile ¹⁾	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
EUROTUBI EUROPA Inox Pressfitting System M-Profile ¹⁾	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Evans Components Presslok	VAU 15 (½")		578630
	VAU 20 (¾")		578632
	VAU 25 (1")		578634
F			
FAR Rubinetterie PRESSFAR	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
F.B.Q. BARONIO BQ press	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 14 45° (PR-2B)	Mini Z1	574532
	V 15 45° (PR-2B)	Mini Z1	574504
	V 16 45° (PR-2B)	Mini Z1	574534
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
F.B.Q. BARONIO BQ press carbon steel	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
F.B.Q. BARONIO BQ press gas	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
Fercofloor DUO Press FERCO PEX	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	TH 40		578624
Fercofloor DUO Press MULTIFER	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	TH 40		578624
	U 16		578374
FILINOX Instalpress Steel	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
FILINOX Instalpress Inox	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
Fittings Estándar ECO-PRESS	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
Fittings Estándar MULTICAPA	RFz 16		578492
	RFz 18		578638
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
Fittings Estándar PE-X	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
FOHS HEIZTECHNIK FOHSPRESS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
FORNARA ForPress	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
FRABO FRABOPRESS 316 GAS M	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
FRABO FRABOPRESS 316 GAS M	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
FRABO FRABOPRESS 316 GAS M	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
FRABO FRABOPRESS 316 GAS V	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
FRABO FRABOPRESS 316 M	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
FRABO FRABOPRESS 316 V	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
FRABO FRABOPRESS CHROME	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
FRABO FRABOPRESS C-STEEL M	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
FRABO FRABOPRESS C-STEEL V	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
FRABO FRABOPRESS GAS M	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
FRABO FRABOPRESS GAS V	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
FRABO FRABOPRESS KOMBI	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
FRABO FRABOPRESS M	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
FRABO FRABOPRESS SOLAR	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
FRABO FRABOPRESS TS	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	M 22		578316
	M 22 45° (PR-2B)	Mini Z1	574526
FRABO FRABOPRESS V	V 22		578334
	V 22 45° (PR-2B)	Mini Z1	574508
	V 12		578324
	V 15		578328
Fränkische alpex-duo	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
Fränkische alpex-duo XS	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 18		578458
	F 20		578460
	F 26		578462
	F 32		578464
Fränkische alpex F50 PROFI	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	F 16		578456
(DN 26)	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	VP 16		578482
	VP 20		578484
	VP 32		578488

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website: www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Fränkische alpeX-gas	F 20		578460
	F 26		578462
	F 32		578464
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
Fränkische alpeX L	Fz 40		578478
G			
gaboTherm H+S	TH 10		578342
	TH 12		578346
	TH 14		578348
	TH 15		578350
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
Gallagher USA YogaPipe ACR	H 12 (¾")		578396
	U 14 (¾")		578372
	U 16 (¾")		578374
	U 18 (¾")		578376
	U 20 (¾")		578378
	U 25 (¾")		578380
	U 32 (1½")		578382
Geberit Mapress C-STÄHL	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Geberit Mapress Edelstahl	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Geberit Mapress Edelstahl Gas	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Geberit Mapress Kupfer	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
Geberit Mapress Kupfer Gas	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Geberit Mepla	G 16		578444
	G 20		578446
	G 26		578448
	G 32		578450
	G 40		578452
Geberit Mepla Therm	G 16		578444
	G 20		578446
	G 26		578448
Geberit Volex	TH 16		578352
	TH 20		578358
	TH 26		578362
General Fittings ST00	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
System	U 32		578382

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
General Fittings Serie 5S00	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
General Fittings Trident	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	B 16		578468
	F 16		578456
	F 16 45° (PR-2B)	Mini Z1	574550
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
General Fittings Trident Gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 32		578382
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
Giacomini Raccordi RM Giacomini	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 32		578382
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
Giacomini RM MULTIGAS	TH 40		578624
	U 16		578374
	U 20		578378
	U 32		578382
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
Giacomini Valvole Giacomini serie R850V	TH 40		578624
	U 16		578374
	U 20		578378
	U 32		578382
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
Golan Pipe Systems (Scandinavia) Alu-Pres	V 35 45° (PR-2B)	Mini Z1	574512
	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
Golan Pipe Systems (Scandinavia) Alu-Pres	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	U 16		578374
	U 20		578378
	U 25		578380
Alu-Pres	U 32		578382
	U 40		578386

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Grinnell G-PRESS Copper Fittings	VUS ½" (OD 15,9 mm)		578566
	VUS ¾" (OD 22,2 mm)		578568
	VUS 1" (OD 28,6 mm)		578570
	VUS 1½" (OD 34,9 mm)		578606
GS Wärmesysteme System TH	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
GS Wärmesysteme System V	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
H			
HakaGerodur HAKASAN	TH 10		578342
	TH 11,6		578344
	TH 12		578346
	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
HASTINIK Hastinik/Hitpress	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
heima24	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
HELIROMA klimapress	TH 40		578624
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
HELIROMA romapress	U 40		578386
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
Henco	RFz 32		578498
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
Herotec TEMPUS-PRESS PLUS	HE 32		578370
	HEz 40 ¹⁾		578572
	H 16		578400
	H 20		578406
	H 25		578408
	H 32		578412
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
HERZ PIPEFIX	U 40		578386
	TH 10		578342
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
HIDRONIX MULTIGAS	TH 40		578624
	TH 16		578352
	TH 20		578358
	TH 26		578362

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
HIDRONIX MULTIPIPE	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	U 14		578372
	U 16		578374
	U 18		578376
HIDRONIX UNICO	U 20		578378
	C 26		578392
	U 32		578382
	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	H 14		578398
	H 16		578400
HITEC Sistema Multistrato	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	C 26		578392
	U 32		578382
Hopewell press fit system	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
hp praski BAVARIA-press	TH 40		578624
	M 15		578312
	M 18		578314
	M 22		578316
IBP >B< Flex	M 28		578318
	M 35		578390
	TH 10		578342
	TH 14		578348
	TH 16		578352
	TH 17		578354
IBP >B< Press	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
IBP >B< Press Carbon	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 14 45° (PR-2B)	Mini Z1	574532
	V 15 45° (PR-2B)	Mini Z1	574504
	V 16 45° (PR-2B)	Mini Z1	574534
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website: www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
IBP >B< Press Gas	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
IBP >B< Press Inox	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
IBP >B< Press Solar	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
ICMA Sempiter	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
	U 40		578386
ICMA Sempigas	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
Idrosanitaria Bonomi	TH 16		578352
	TH 20		578358
	TH 26		578362
Idrosanitaria Bonomi	TH 16		578352
	TH 18		578356
	TH 20		578358
Idropress	TH 26		578362
	TH 32		578364
	TH 40		578624
IDROSISTEMI Ta-Press	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	Fz 40		578478
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
	U 40		578386
IDROTRADE Storm Multipinza	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
IDROTRADE Storm Multistrato	TH 40		578624
	U 16		578374
	U 20		578378
	U 40		578386
	H 14		578398
	H 16		578400
	H 20		578406
	H 26		578410
IDROTRADE StormPRES	H 32		578412
	U 40		578386
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
IDROTRADE StormSTEEL	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
ILTA INOX/CHIBRO Pressfitting Cuni	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
ILTA INOX/CHIBRO Pressfitting inox	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Instantor Copper Press Imperial	VI ½" (OD 14,7 mm)		578716
	VI ¾" (OD 21,0 mm)		578718
	VI 1" (OD 27,4 mm)		578720
Instantor Copper Press Metric	M 15		578312
	M 22		578316
	M 28		578318
Instantor Press System	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
IPA IPANA Press	TH 10		578342
	TH 11,6		578344
	TH 12		578346
	TH 14		578348
	TH 15		578350
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 22		578588
	TH 25		578360
	TH 26		578362
	TH 28		578590
	TH 32		578364
	TH 40		578624
IPA THu IPANA Press	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
IPALPEX (Industrie du Plastique et Accessoires)	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	THL 32		578368
	TH 40		578624
IPLEX PIPELINES AUSTRALIA Iplex Pro-fit	K16/P18		578592
IPLEX PIPELINES AUSTRALIA Iplex K1 (Gas)	K16/P18		578592
	K/20		578594
	K/25		578596
	K32		578598
IPLEX PIPELINES AUSTRALIA Iplex K2	K1/40		578600
	K16/P18		578592
	K/20		578594
	K/25		578596
ISOTUBI NUMEPRESS	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
IVAR ALPEX-GAS	B 20		578472
	B 26		578474
	B 32		578476
IVAR Ivar-Press	B 14		578466
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476
	Fz 40		578478
IVAR MULTI PRESS GAS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
IVAR MULTI PRESS GAS ITALIA	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	U 32		578382
IVAR Multi Press MP	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
	F 16		578456
	F 18		578458
	F 20		578460
	F 26		578462
	F 32		578464
	Fz 40		578478
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	C 26		578392
	U 32		578382
	U 40		578386
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476
IVAR Multi Press Leak (MPL)	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
IVAR Plastic Multi Press PMP	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	U 25		578380
	C 26		578392
	U 32		578382
	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
IVAR Plastic Multi Press Leak (PMPL)	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
IVT Edelstahl- Presssystem	C 26		578392
	U 32		578382
	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
IVT PRIPRESS	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
J			
Jäger - Aquatec Aquapress H	H 14		578398
	H 16		578400
	H 17		578402
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	U 40		578386
Jäger - Aquatec C-Stahl Press Typ M	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Jäger - Aquatec Edelstahl Press Typ M	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Jäger - Aquatec Kupfer Press Typ V	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
Jansen AG JANSEN prima	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
Jaraflex- Presssystem	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For taking suitable pressing inserts.
- Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website:

www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
JUNGWOO JWPress	VUS ½" (OD 15,9 mm) VUS ¾" (OD 22,2 mm) VUS 1" (OD 28,6 mm) VUS 1¼" (OD 34,9 mm)		578566 578568 578570 578606
K			
KAN KAN-therm Press	U 16 U 20 U 25 C 26 U 32 U 40		578374 578378 578380 578392 578382 578386
KAN KAN-therm Press LBP	TH 14 TH 16 TH 20 TH 25 TH 26 TH 32 TH 40 U 14 U 16 U 20 U 25 C 26 U 32 U 40		578348 578352 578358 578360 578362 578364 578624 578372 578374 578378 578380 578392 578382 578386
KAN KAN-therm Inox	M 12 M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35 M 12 45° (PR-2B) M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578310 578312 578314 578316 578318 578390 574520 574522 574524 574526 574528 574530
KAN KAN-therm Steel	M 12 M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35 M 12 45° (PR-2B) M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578310 578312 578314 578316 578318 578390 574520 574522 574524 574526 574528 574530
KE KELIT KELIT KELOX	U 16 U 18 U 20 U 25 U 32 U 40		578374 578376 578378 578380 578382 578386
KE KELIT COPPERFIX Kupfer	M 15 M 18 M 22 M 28 M 35 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578312 578314 578316 578318 578390 574522 574524 574526 574528 574530
KE KELIT steelFIX C-Stahl	M 15 M 18 M 22 M 28 M 35 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578312 578314 578316 578318 578390 574522 574524 574526 574528 574530
KE KELIT steelFIX Edelstahl	M 15 M 18 M 22 M 28 M 35 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578312 578314 578316 578318 578390 574522 574524 574526 574528 574530
KEMBLA KemPress (AUS)	VAU 15 (OD 12,7 mm) VAU 20 (OD 19,1 mm) VAU 25 (OD 25,4 mm) VAU 32 (OD 31,8 mm)		578630 578632 578634 578636
KEMBLA KemPress Gas (AUS)	VAU 15 (OD 12,7 mm) VAU 20 (OD 19,1 mm) VAU 25 (OD 25,4 mm) VAU 32 (OD 31,8 mm)		578630 578632 578634 578636
KISAN Kisan KD	KI 16 KI 20 KI 25 TH 16 TH 20 TH 25		578524 578526 578528 578352 578358 578360
KISAN Kisan WL	KI 16 KI 20 KI 25 KI 32 TH 16 TH 20 TH 25 TH 32		578524 578526 578528 578530 578352 578358 578360 578364

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
KISAN Kisan WM	KI 16 KI 20 KI 25 KI 32		578524 578526 578528 578530
KISAN Kisan WR	U 20 U 25 U 32 U 40 TH 20 TH 25 TH 32 TH 40		578378 578380 578382 578386 578358 578360 578364 578624
KISAN Kistal C	M 15 M 18 M 22 M 28 M 35 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578312 578314 578316 578318 578390 574522 574524 574526 574528 574530
KISAN Kistal Inox	M 15 M 18 M 22 M 28 M 35 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578312 578314 578316 578318 578390 574522 574524 574526 574528 574530
KME cuprotherm CTX	TH 14 TH 16 TH 18 TH 20 TH 26		578348 578352 578356 578358 578362
KME QTEC - Comap SkinPress	TH 14 TH 16 TH 20 TH 26		578348 578352 578358 578362
KME QTEC - Oventrop Cofit	H 16 A H 20 A H 26 A		578420 578426 578430
L			
LEGEND-PRESS press fitting system	VUS ½" (OD 15,9 mm) VUS ¾" (OD 22,2 mm) VUS 1" (OD 28,6 mm) VUS 1¼" (OD 34,9 mm)		578566 578568 578570 578606
LK Systems LK >B<Press	V 12 V 15 V 18 V 22 V 28 V 35 V 12 45° (PR-2B) V 15 45° (PR-2B) V 18 45° (PR-2B) V 22 45° (PR-2B) V 28 45° (PR-2B) V 35 45° (PR-2B)		578324 578328 578332 578334 578336 578604 574502 574504 574506 574508 574510 574512
LK Systems LK >B<Press Elförzinkat	V 12 V 15 V 18 V 22 V 28 V 35 V 12 45° (PR-2B) V 15 45° (PR-2B) V 18 45° (PR-2B) V 22 45° (PR-2B) V 28 45° (PR-2B) V 35 45° (PR-2B)		578324 578328 578332 578334 578336 578604 574502 574504 574506 574508 574510 574512
LK Systems LK >B<Press Gas	V 15 V 18 V 22 V 28 V 35 V 15 45° (PR-2B) V 18 45° (PR-2B) V 22 45° (PR-2B) V 28 45° (PR-2B) V 35 45° (PR-2B)		578328 578332 578334 578336 578604 574504 574506 574508 574510 574512
LK Systems LK Universal	TH 16 TH 20 TH 25 TH 32 TH 40		578352 578358 578360 578364 578624
LVI-DAHL Altech-Aluapex	U 16 U 20 U 25 U 32		578374 578378 578380 578382
M			
MAINCOR MAINPRESS	U 16 U 20 U 25 U 32 U 40		578374 578378 578380 578382 578386
MAINCOR MAINFLOr	U 16 U 20		578374 578378
Mair Heiztechnik M-Press	H 11,5 TH 16 TH 20 TH 26 TH 32 TH 40		578394 578352 578358 578362 578364 578624

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	
Ma.s.ter System PRESSMASTER	TH 14		578348	
	TH 16		578352	
	TH 18		578356	
	TH 20		578358	
	TH 25		578360	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	H 14		578398	
	H 16		578400	
	H 18		578404	
	H 20		578406	
	H 26		578410	
	H 32		578412	
	U 14		578372	
	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
	U 32		578382	
U 40		578386		
Meier Tobler Metalplast - Stramax	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
	U 32		578382	
METALGRUP Permatubo	U 16		578374	
	U 18		578376	
	U 20		578378	
	U 25		578380	
	U 32		578382	
METALGRUP PexGrup	U 40		578386	
	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
METALGRUP PexGrup	RFz 32		578498	
	METALGRUP MultiGrup	U 16		578374
		U 18		578376
U 20			578378	
U 25			578380	
Mueller Industries Streamline PRS	U 32		578382	
	VUS ½" (OD 15,9 mm)		578566	
	VUS ¾" (OD 22,2 mm)		578568	
	VUS 1" (OD 28,6 mm)		578570	
MULTITHERM PRESSSYSTEM	VUS 1½" (OD 34,9 mm)		578606	
	TH 16		578352	
	TH 20		578358	
	TH 26		578362	
Multicapas Industrial AIS PEX	TH 32		578364	
	TH 40		578624	
	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
	RFz 32		578498	
	U 16		578374	
Multicapas Industrial multitubo systems MC	U 20		578378	
	U 25		578380	
	U 32		578382	
	U 40		578386	
	U 16		578374	
	U 18		578376	
	U 20		578378	
Multicapas Industrial multitubo systems MM	U 25		578380	
	U 32		578382	
	U 40		578386	
	H 16		578400	
	H 20		578406	
	H 25		578408	
	H 26		578410	
	H 32		578412	
	RFz 16		578492	
	RFz 20		578494	
	RFz 25		578496	
	RFz 32		578498	
	TH 16		578352	
	TH 20		578358	
	TH 25		578360	
	TH 26		578362	
	TH 32		578364	
	TH 40		578624	
	U 16		578374	
	U 20		578378	
U 25		578380		
U 32		578382		
U 40		578386		
N				
NEUTHERM MEKUPRESS-HT	H 16		578400	
	H 20		578406	
	H 26		578410	
	H 32		578412	
NIBCO (USA) Press System Copper	VUS ½" (OD 15,9 mm)		578566	
	VUS ¾" (OD 22,2 mm)		578568	
	VUS 1" (OD 28,6 mm)		578570	
	VUS 1½" (OD 34,9 mm)		578606	

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Nicolli Fluxo	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
NUPI Industrie Italiane Multinupi	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 18		578458
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
C 26		578392	
U 32		578382	
U 40		578386	
Nussbaum Optifitt-Press	VMP ¾" (OD 17,2 mm)		578660
	VMP ½" (OD 21,3 mm)		578662
Nussbaum Optiflex-Flowpress	VRX 16		578640
	VRX 20		578642
	VRX 25		578644
	VRX 32		578646
Nussbaum Optipress Aquadplus	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
Nussbaum Optipress Gaz	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
V 35 45° (PR-2B)	Mini Z1	574512	
Nussbaum Optipress-Therm	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
V 35 45° (PR-2B)	Mini Z1	574512	
O			
O.M.T. - Press	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
Oventrop Cofit P	H 16 A		578420
	H 20 A		578426
	H 26 A		578430
	H 32 A		578432
Oventrop Cofit PD	H 16 A		578420
	H 20 A		578426
	H 26 A		578430
Oventrop Cofit PDK	H 16 A		578420
	H 20 A		578426
Oventrop Cofit PD-HT	H 16 A		578420
	H 20 A		578426
Oventrop Cofit PDK-HT	H 16 A		578420
	H 20 A		578426

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

¹⁾ Only pressing tongs from designation “108” (1st quarter of 2008), “208” (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

2) For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation “117” (1st quarter of 2017), “217” (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website:

www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
P			
PBTub SERTIPRESS	RFz 12 RFz 16 RFz 20 RFz 25		578490 578492 578494 578496
PBTub SERTI-STEEL ¹⁾	M 15 M 18 M 22 M 28 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B)		578312 578314 578316 578318 574522 574524 574526 574528
Pegler Yorkshire XPress Carbon	M 12 M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35 M 12 45° (PR-2B) M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578310 578312 578314 578316 578318 578390 574520 574522 574524 574526 574528 574530
Pegler Yorkshire XPress Copper	M 12 M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35 M 12 45° (PR-2B) M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578310 578312 578314 578316 578318 578390 574520 574522 574524 574526 574528 574530
Pegler Yorkshire XPress Copper Gas	M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35		578312 578314 578316 578318 578390
Pegler Yorkshire XPress Stainless	M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578312 578314 578316 578318 578390 574522 574524 574526 574528 574530
Pegler Yorkshire XPress Stainless Gas	M 15 M 18 ¹⁾ M 22 M 28 ¹⁾ M 35		578312 578314 578316 578318 578390
PERFEXIM PERFEKT SYSTEM	U 16 U 20 U 25 U 32		578374 578378 578380 578382
PERFILTUBO PERFILALUPEX	U 16 U 18 U 20 U 25 U 32 U 40		578374 578376 578378 578380 578382 578386
PERFILTUBO PERFILPRESS	M 15 M 18 M 22 M 28 M 35 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578312 578314 578316 578318 578390 574522 574524 574526 574528 574530
PEXTUBE PexTube	RFz 16 RFz 20 RFz 25 RFz 32		578492 578494 578496 578498
Pipelife C-PRESS	M 15 M 18 M 22 M 28 M 35 M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		578312 578314 578316 578318 578390 574522 574524 574526 574528 574530
Pipelife RADOPRESS	TH 16 TH 18 TH 20 TH 26 TH 32 TH 40		578352 578356 578358 578362 578364 578624
Pipetec Connect	TH 16 TH 20 TH 26 TH 32 TH 40		578352 578358 578362 578364 578624
PLASTICA ALFA Multypex	TH 16 TH 20 TH 26 TH 32		578352 578358 578362 578364
PLASTICA ALFA Multypex Air	TH 16 TH 20 TH 26 TH 32		578352 578358 578362 578364
PLASTICA ALFA Multypexalfa Gas	TH 16 TH 20 TH 26		578352 578358 578362

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
PLASTICA ALFA Multypexalfa Gas protek	TH 16 TH 20 TH 26		578352 578358 578362
PLASTICA ALFA Multypex Plus	TH 16 TH 20 TH 26 TH 32		578352 578358 578362 578364
PLASTICA ALFA Multypex Thermo	TH 16 TH 20 TH 26 TH 32		578352 578358 578362 578364
PLASTICA ALFA Multypex Thermo Plus	TH 16 TH 20 TH 26 TH 32		578352 578358 578362 578364
PLÁSTICOS FERRO FERROPLAST GPF MC PRESS Pressfitting MULTICAPA	U 16 U 20 U 25 U 32		578374 578378 578380 578382
PLÁSTICOS FERRO FERROPLAST GPF PPSU Pressfitting PE-X y MULTICAPA	U 16 U 20 U 25 U 32		578374 578378 578380 578382
PLÁSTICOS FERRO FERROPLAST GPF PRESS Pressfitting PE-X	RFz 16 RFz 20 RFz 25 RFz 32		578492 578494 578496 578498
PLUMBING PLUS EZIPEX Crimp (AUS)	K16/P18 K20 K25 K32 K1/40		578592 578594 578596 578598 578600
PLUMBING PLUS EZIPEX Gas (AUS)	K16/P18 K20 K25 K32 K1/40		578592 578594 578596 578598 578600
PLUMBING PLUS EZIPRESS Gas (AUS)	VAU 15 (OD 12,7 mm) VAU 20 (OD 19,1 mm) VAU 25 (OD 25,4 mm) VAU 32 (OD 31,8 mm) VAU 15 45° (PR-2B) (OD 12,7 mm) VAU 20 45° (PR-2B) (OD 19,1 mm) VAU 25 45° (PR-2B) (OD 25,4 mm)		578630 578632 578634 578636 574540 574542 574544
PLUMBING PLUS EZIPRESS Solar (AUS)	VAU 15 (OD 12,7 mm) VAU 20 (OD 19,1 mm) VAU 25 (OD 25,4 mm) VAU 15 45° (PR-2B) (OD 12,7 mm) VAU 20 45° (PR-2B) (OD 19,1 mm) VAU 25 45° (PR-2B) (OD 25,4 mm)		578630 578632 578634 574540 574542 574544
PLUMBING PLUS EZIPRESS Water (AUS)	VAU 15 (OD 12,7 mm) VAU 20 (OD 19,1 mm) VAU 25 (OD 25,4 mm) VAU 32 (OD 31,8 mm) VAU 15 45° (PR-2B) (OD 12,7 mm) VAU 20 45° (PR-2B) (OD 19,1 mm) VAU 25 45° (PR-2B) (OD 25,4 mm)		578630 578632 578634 578636 574540 574542 574544
POLYPIPE POLYSURE	TH 10 TH 15 TH 22 TH 28		578342 578350 578588 578590
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 15 M 18 M 22 M 28 M 35		578312 578314 578316 578318 578390
POLYSAN- C Stahl-Press- System M	M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		574522 574524 574526 574528 574530
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 15 M 18 M 22 M 28 M 35		578312 578314 578316 578318 578390
POLYSAN- Edelstahl Press-System 1.4520	M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		574522 574524 574526 574528 574530
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 15 M 18 M 22 M 28 M 35		578312 578314 578316 578318 578390
POLYSAN- Edelstahl Press-System Gas	M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		574522 574524 574526 574528 574530
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	M 15 M 18 M 22 M 28 M 35		578312 578314 578316 578318 578390
POLYSAN- Edelstahl Press-System Wasser	M 15 45° (PR-2B) M 18 45° (PR-2B) M 22 45° (PR-2B) M 28 45° (PR-2B) M 35 45° (PR-2B)		574522 574524 574526 574528 574530
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Öster- reich)	TH 14 TH 16 TH 17 TH 18 TH 20 TH 26 TH 32 TH 40		578348 578352 578354 578356 578358 578362 578364 578624

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
POLYSAN Handelsges. m.b.H. & Co KG (Krems/Österreich)	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
POLYSAN-Henco-Press-System	TH 26		578362
	HE 32		578370
	HEz 40 ³⁾		578572
	U 16		578374
	U 18		578376
POLYSAN (España) „Rainbow“	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
Prandelli Multyrama Pf	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
Prandelli Multyrama Pfm	H 32		578412
	U 40		578386
	H 16		578400
	H 18		578404
	H 20		578406
PURMO Cleverfit Radial	H 26		578410
	H 32		578412
	TH 16		578352
	TH 17		578354
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 16		578374
	U 18		578376
	U 20		578378
	U 40		578386
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 16		578374
	U 20		578378
	U 32		578382
	VP 16		578482
	VP 20		578484
	VP 32		578488
R			
Raccorderie Metalliche aesPRES ¹⁾	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Raccorderie Metalliche inoxPRES ¹⁾	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Raccorderie Metalliche MARINEPRES ¹⁾	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Raccorderie Metalliche steelPRES ¹⁾	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
RBM Tita-fix	B 14		578466
	B 16		578468
	B 18		578470
	B 20		578472
	B 26		578474
	F 16		578456
	F 18		578458
	F 20		578460
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	H 14		578398
	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	U 32		578382
	U 40		578386
RBM Tita-gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
Redi Nicoll Fluxo	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
Redi Nicoll Fluxo Gas	TH 16		578352
	TH 20		578358
	TH 26		578362
RIFENG LD PRESS FITTING (F8)	LD 16		578652
	LD 20		578654
	LD 25		578656
RIFENG U PRESS FITTING (F5)	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
RIFENG TH PRESS FITTING (F9)	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
RIQUIER A SERTIR	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
Roth PressCheck	RN 14		578434
	RN 16		578454
	RN 17		578436
	RN 20		578438
	RN 25/26		578440
	RN 32		578442
Roth Ibérica Rothapress	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 32		578364
	TH 40		578624
Rubinetteria Bresciane Bonomi TURBO INOX	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Rubinetteria Bresciane Bonomi TURBO STEEL	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
Rubinetteria Bresciane Bonomi TURBO PRESS	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
Rubinetteria Bresciane Bonomi TURBO PRESS GAS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

¹⁾ Only pressing tongs from designation “108” (1st quarter of 2008), “208” (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation “117” (1st quarter of 2017), “217” (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website:

www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
S			
SA.MI plastic	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
SA.MI plastic Multistrato Gas	TH 40		578624
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
SANHA 3fit-Press Pb-free Serie 25000	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	Fz 40		578478
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
	U 40		578386
SANHA 3fit-Press PPSU Serie 35000	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
SANHA-NiroSan Gas Presssystem Serie 17000	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 15 ¹⁾		578328
	V 18 ¹⁾		578332
SANHA-NiroSan Industry Presssystem Serie 18000	V 22 ¹⁾		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
SANHA-NiroSan- Presssystem Serie 9000	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 15 ¹⁾		578328
	V 18 ¹⁾		578332
	V 22 ¹⁾		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
SANHA-NiroSan SF Presssystem Serie 19000 (silicone free)	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 15 ¹⁾		578328
	V 18 ¹⁾		578332
SANHA NiroTherm Serie 91000	V 22 ¹⁾		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
SANHA NiroTherm Industry Serie 98000	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 15 ¹⁾		578328
	V 18 ¹⁾		578332
	V 22 ¹⁾		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.	System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
SANHA-Press Chrom Serie 16000	SA 12		578510	SANHA-Press SOLAR Pressfittings Serie 12000/ Serie 13000	SA 12		578510
	SA 15		578514		SA 15		578514
	SA 18		578518		SA 18		578518
	SA 22		578520		SA 22		578520
	SA 28		578522		SA 28		578522
	M 12		578310		M 12		578310
	M 15 ¹⁾		578312		M 15 ¹⁾		578312
	M 18 ¹⁾		578314		M 18 ¹⁾		578314
	M 22 ¹⁾		578316		M 22 ¹⁾		578316
	M 28		578318		M 28		578318
	M 12 45° (PR-2B)	Mini Z1	574520		M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522		M 12 45° (PR-2B)	Mini Z1	574520
	M 18 45° (PR-2B)	Mini Z1	574524		M 15 45° (PR-2B)	Mini Z1	574522
	M 22 45° (PR-2B)	Mini Z1	574526		M 18 45° (PR-2B)	Mini Z1	574524
	M 28 45° (PR-2B)	Mini Z1	574528		M 22 45° (PR-2B)	Mini Z1	574526
	V 12		578324		M 28 45° (PR-2B)	Mini Z1	574528
	V 15 ¹⁾		578328		M 35 45° (PR-2B)	Mini Z1	574530
	V 18 ¹⁾		578332		V 12		578324
	V 22 ¹⁾		578334		V 15 ¹⁾		578328
	V 28		578336		V 18 ¹⁾		578332
	V 12 45° (PR-2B)	Mini Z1	574502		V 22 ¹⁾		578334
	V 15 45° (PR-2B)	Mini Z1	574504		V 28		578336
	V 18 45° (PR-2B)	Mini Z1	574506		V 35		578604
	V 22 45° (PR-2B)	Mini Z1	574508		V 12 45° (PR-2B)	Mini Z1	574502
	V 28 45° (PR-2B)	Mini Z1	574510		V 15 45° (PR-2B)	Mini Z1	574504
SANHA-Press GAS Pressfittings Serie 10000/ Serie 11000	SA 12		578510	SANHA PURAPRESS Serie 8000	SA 12		578510
	SA 14		578512		SA 14		578512
	SA 15		578514		SA 15		578514
	SA 16		578516		SA 16		578516
	SA 18		578518		SA 18		578518
	SA 22		578520		SA 22		578520
	SA 28		578522		SA 28		578522
	M 12		578310		M 12 ¹⁾		578310
	M 15 ¹⁾		578312		M 15 ¹⁾		578312
	M 18 ¹⁾		578314		M 18 ¹⁾		578314
	M 22 ¹⁾		578316		M 22 ¹⁾		578316
	M 28		578318		M 28 ¹⁾		578318
	M 35		578390		M 35 ¹⁾		578390
	M 12 45° (PR-2B)	Mini Z1	574520		M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522		M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524		M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526		M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528		M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530		M 35 45° (PR-2B)	Mini Z1	574530
	V 12		578324		V 12		578324
	V 14		578326		V 14		578326
	VG 16		578340		VG 14		578338
	V 15 ¹⁾		578328		V 15 ¹⁾		578328
	V 16		578330		V 16		578330
	VG 16		578340		VG 16		578340
	V 18 ¹⁾		578332		V 18 ¹⁾		578332
	V 22 ¹⁾		578334		V 22 ¹⁾		578334
	V 28		578336		V 28		578336
	V 35		578604		V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502		V 12 45° (PR-2B)	Mini Z1	574502
	VG 14 45° (PR-2B)	Mini Z1	574536		VG 14 45° (PR-2B)	Mini Z1	574536
	V 15 45° (PR-2B)	Mini Z1	574504		V 15 45° (PR-2B)	Mini Z1	574504
	VG 16 45° (PR-2B)	Mini Z1	574538		VG 16 45° (PR-2B)	Mini Z1	574538
	V 18 45° (PR-2B)	Mini Z1	574506		V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508		V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510		V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512		V 35 45° (PR-2B)	Mini Z1	574512
SANHA-Press Pressfittings Serie 6000	SA 12		578510	SANHA-Therm Serie 24000	SA 12		578510
	SA 14		578512		SA 15		578514
	SA 15		578514		SA 18		578518
	SA 16		578516		SA 22		578520
	SA 18		578518		SA 28		578522
	SA 22		578520		M 12		578310
	SA 28		578522		M 15 ¹⁾		578312
	M 12		578310		M 18 ¹⁾		578314
	M 15 ¹⁾		578312		M 22 ¹⁾		578316
	M 18 ¹⁾		578314		M 28		578318
	M 22 ¹⁾		578316		M 35		578390
	M 28		578318		M 12 45° (PR-2B)	Mini Z1	574520
	M 35		578390		M 15 45° (PR-2B)	Mini Z1	574522
	M 12 45° (PR-2B)	Mini Z1	574520		M 18 45° (PR-2B)	Mini Z1	574524
	M 15 45° (PR-2B)	Mini Z1	574522		M 22 45° (PR-2B)	Mini Z1	574526
	M 18 45° (PR-2B)	Mini Z1	574524		M 28 45° (PR-2B)	Mini Z1	574528
	M 22 45° (PR-2B)	Mini Z1	574526		M 35 45° (PR-2B)	Mini Z1	574530
	M 28 45° (PR-2B)	Mini Z1	574528		V 12		578324
	M 35 45° (PR-2B)	Mini Z1	574530		V 15 ¹⁾		578328
	V 12		578324		V 18 ¹⁾		578332
	V 14		578326		V 22 ¹⁾		578334
	VG 14		578338		V 28		578336
	V 15 ¹⁾		578328		V 35		578604
	V 16		578330		V 12 45° (PR-2B)	Mini Z1	574502
	VG 16		578340		VG 14 45° (PR-2B)	Mini Z1	574536
	V 18 ¹⁾		578332		V 15 45° (PR-2B)	Mini Z1	574504
	V 22 ¹⁾		578334		VG 16 45° (PR-2B)	Mini Z1	574538
	V 28		578336		V 18 45° (PR-2B)	Mini Z1	574506
	V 35		578604		V 22 45° (PR-2B)	Mini Z1	574508
	V 12 45° (PR-2B)	Mini Z1	574502		V 28 45° (PR-2B)	Mini Z1	574510
	VG 14 45° (PR-2B)	Mini Z1	574536		V 35 45° (PR-2B)	Mini Z1	574512
	V 15 45° (PR-2B)	Mini Z1	574504				
	VG 16 45° (PR-2B)	Mini Z1	574538				
	V 18 45° (PR-2B)	Mini Z1	574506				
	V 22 45° (PR-2B)	Mini Z1	574508				
	V 28 45° (PR-2B)	Mini Z1	574510				
	V 35 45° (PR-2B)	Mini Z1	574512				

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

- ¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- ²⁾ For taking suitable pressing inserts.
- ³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website: www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
SANHA-Therm Industry Serie 28000	SA 12		578510
	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522
	M 12		578310
	M 15 ¹⁾		578312
	M 18 ¹⁾		578314
	M 22 ¹⁾		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 12		578324
	V 15 ¹⁾		578328
	V 18 ¹⁾		578332
	V 22 ¹⁾		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
SANITOP PERMATUBO INOX	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
SANPRO THPRESS	M 35 45° (PR-2B)	Mini Z1	574530
	TH 16		578352
	TH 20		578358
	TH 26		578362
SATEC SK ViTerm	TH 32		578364
	TH 16		578352
	TH 18		578356
	TH 20		578358
Schütz duo-flex tri-o-flex	TH 26		578362
	TH 32		578364
	U 40		578386
	TH 14		578348
	TH 16		578352
Schwer Fittings AQUApress	TH 17		578354
	TH 20		578358
	TH 25		578360
	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
Seppelfricke VSH SudoPress C-Stahl Visu-Control	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
Seppelfricke Seppelfricke VSH SudoPress Edelstahl Visu-Control	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
Seppelfricke VSH SudoPress Kupfer Visu-Control	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
Seppelfricke VSH SudoPress Kupfer Gas Visu-Control	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Seppelfricke VSH SudoPress Kupfer Solar Visu-Control	V 15		578328
	V 18		578332
	V 22		578334
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	M 12		578310
	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
Seppelfricke VSH XPress C-Stahl	M 28 ¹⁾		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	M 15		578312
	M 18 ¹⁾		578314
Seppelfricke VSH XPress Edelstahl	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	M 15		578312
	M 18 ¹⁾		578314
Seppelfricke VSH XPress Kupfer	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	M 15		578312
Seppelfricke VSH XPress Kupfer gas	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 16		578352
SESTA SESTA GAS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	H 16		578400
	H 20		578406
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
SESTA sistema multistrato	TH 26		578362
	TH 32		578364
	TH 40		578624
	U 16		578374
	U 20		578378
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	U 16		578374
SIGMA LI Premium	U 20		578378
	U 25		578380
	U 32		578382
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	U 16		578374
	U 20		578378
	U 25		578380
SLOVARM PEX-THERM	U 32		578382
	U 16		578374
	U 20		578378
	H 26		578410
	U 32		578382
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	H 16		578400
STANDARD HIDRAULICA MultiStandard	H 20		578406
	H 25		578408
	H 32		578412
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
	TH 16		578352
	TH 20		578358
	TH 25		578360
STELBI Polikraft	TH 32		578364
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	H 16		578400
	H 20		578406
	H 26		578410

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
STELBI	TH 16		578352
Stelgas	TH 20		578358
	TH 26		578362
STPC STPEX	TH 16		578352
	TH 20		578358
	TH 26		578362
System Ewoprex	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 32		578382
System WELCO-Gas	H 16 A		578420
	H 20 A		578426
	H 26 A		578430
	H 32 A		578432
System WOPREX	H 14 A		578418
	H 16 A		578420
	H 17 A		578422
	H 20 A		578426
	H 26 A		578430
	H 32 A		578432
T			
TDM BRASS Serie 1600	H 16		578400
	H 18		578404
	H 20		578406
	H 25		578408
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	THL 32		578368
	TH 40		578624
	U 16		578374
	U 18		578376
	U 20		578378
	U 25		578380
	C 26		578392
	U 32		578382
TDM BRASS Serie 1700 gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	THL 32		578368
TermoConcept TC-PRESS	Basic E01 ¹⁾		578618
THERMOLUTZ	H 14		578398
	H 16		578400
	TH 20		578358
TE-SA	TH 14		578348
TE-SA press serie 800	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
TIEMME AL-COBRAPEX Serie 1650	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 25		578360
	TH 26		578362
	THL 32		578368
	TH 40		578624
TIEMME Serie 1700 PE-X a pressare	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
TIEMME TIEMME Gas	TH 16		578352
	TH 20		578358
	TH 26		578362
	THL 32		578368
TIGRE ALPEX GÁS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
TKM Systemtechnik	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
TRA	U 16		578374
MULTITRAPRESS	U 18		578376
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
TRA TRAPRESS	H 12		578396
	H 16		578400
	H 20		578406
	H 25		578408
	H 32		578412
	RFz 12		578490
	RFz 16		578492
	RFz 20		578494
	RFz 25		578496
	RFz 32		578498
TUBIPLAST ITALY MULTILAYER PIPE	H 16		578400
	H 18		578404
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 18		578376
	U 20		578378
	C 26		578392
	U 32		578382
TUBIPLAST ITALY MULTILAYER PIPE GAS SYSTEM	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
TWEETOP	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
U			
UNICAL AG MAX-MULTIPEX	U 16		578374
	U 20		578378
	H 26		578410
	C 26		578392
	U 32		578382
UNIDELTA DeltaII	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	U 32		578382
	U 40		578386
UNIDELTA DeltaII GAS	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 16		578374
	U 20		578378
	U 32		578382
Uponor MLC	UP 14		578576
	UP 16		578578
	UP 18		578580
	UP 20		578582
	UP 25		578584
	UP 32		578586
	U 40		578386
Uponor MLC-D	UP 16		578578
	UP 20		578582
	UP 25		578584
	UP 32		578586
Uponor MLC-G	UP 20		578582
	UP 25		578584
	UP 32		578586
Uponor S-Press PLUS	UP 16		578578
	UP 20		578582
	UP 25		578584
	UP 32		578586
Uponor Uni Pipe PLUS	UP 16		578578
	UP 20		578582
	UP 25		578584
	UP 32		578586

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website: www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini
REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
V			
Valsir Bravopress	B 16		578468
	B 20		578472
	B 26		578474
	B 32		578476
	F 16		578456
	F 20		578460
	F 26		578462
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	H 32 V		578602
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
Valsir PEXAL	H 14		578398
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	H 32 V		578602
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	C 26		578392
	U 32		578382
Van Marcke NV Tubipex	TH 16		578352
	TH 17		578354
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
Van Marcke NV Tubipress	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
Variotherm System TH	TH 11,6		578344
	TH 16		578352
	TH 20		578358
VESBO VP PREMIUM	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
Viega Fonterra	VX 12		578550
	VP 14/15		578480
	VP 16/17		578482
	VP 20		578484
	VP 25		578486
Viega Megapress	VMP ¾" (OD 17,2 mm)		578660
	VMP ½" (OD 21,3 mm)		578662
Viega MegapressS	VMP ¾" (OD 17,2 mm)		578660
	VMP ½" (OD 21,3 mm)		578662
Viega Pexfit	VX 16		578552
	VX 20		578554
	VX 25		578556
Viega Pexfit Fosta G	VX 16		578552
	VX 20		578554
	VX 25		578556
Viega Prestabo	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
Viega Profipress	V 12		578324
	VG 14		578338
	V 15		578328
	VG 16		578340
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	VG 14 45° (PR-2B)	Mini Z1	574536
	V 15 45° (PR-2B)	Mini Z1	574504
	VG 16 45° (PR-2B)	Mini Z1	574538
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
Viega Profipress G	V 12		578324
	VG 14		578338
	V 15		578328
	VG 16		578340
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	VG 14 45° (PR-2B)	Mini Z1	574536
	V 15 45° (PR-2B)	Mini Z1	574504
	VG 16 45° (PR-2B)	Mini Z1	574538
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
Viega Profipress S	V 35 45° (PR-2B)	Mini Z1	574512
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
Viega Profipress Therm	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
Viega ProPress System USA	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
Viega ProPress System USA	V 35 45° (PR-2B)	Mini Z1	574512
	VUS ½" (OD 15,9 mm)		578566
	VUS ¾" (OD 22,2 mm)		578568
	VUS 1" (OD 28,6 mm)		578570
Viega ProPress System USA	VUS 1¼" (OD 34,9 mm)		578606
	VAU 15 (OD 12,7 mm)		578630
	VAU 20 (OD 19,1 mm)		578632
	VAU 25 (OD 25,4 mm)		578634
Viega ProPressG System AUS	VAU 32 (OD 31,8 mm)		578636
	VAU 15 (OD 12,7 mm)		578630
Viega ProPressG System AUS	VAU 20 (OD 19,1 mm)		578632
	VAU 25 (OD 25,4 mm)		578634
Viega ProPressG System AUS	VAU 32 (OD 31,8 mm)		578636
Viega Raxinox	VRX 16		578640
	VRX 20		578642
Viega Raxofix	VRX 16		578640
	VRX 20		578642
	VRX 25		578644
	VRX 32		578646
	VRX 32		578646
Viega Sanfix	VP 16/17		578482
	VP 20		578484
	VP 25		578486
	VP 32		578488
Viega Sanfix Fosta	VP 16/17		578482
	VP 20		578484
	VP 25		578486
	VP 32		578488
Viega Sanpress	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
Viega Sanpress Inox	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	V 15		578328
	V 18		578332
	V 22		578334
Viega Sanpress Inox G	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	V 15		578328
	V 18		578332
	V 22		578334
Viega Smartpress	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
Viessmann	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	VX 16		578552
	VX 20		578554
	VX 25		578556
Vogel & Noot EASYTEC	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624

REMS pressing tongs Mini REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
VSH MultiPress	U 14		578372
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 26		578362
	TH 32		578364
	TH 40		578624
VSH SudoPress Carbon	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
VSH SudoPress Copper	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 14 45° (PR-2B)	Mini Z1	574532
	V 15 45° (PR-2B)	Mini Z1	574504
	V 16 45° (PR-2B)	Mini Z1	574534
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
VSH SudoPress Copper Gas	V 12		578324
	V 14		578326
	V 15		578328
	V 16		578330
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
VSH SudoPress Stainless	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
VSH XPress Carbon	M 12		578310
	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
VSH XPress Copper	M 12		578310
	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
VSH XPress Copper GAS	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
VSH XPress Stainless	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
VSH XPress Stainless Gas	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 15		578312
	M 18 ¹⁾		578314
	M 22		578316
	M 28 ¹⁾		578318
	M 35		578390
W			
Watts MTR Art press	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
WATTS RADIANT	US ¾"		578534
Watts WaterPEX	US ½"		578536
	US ¾"		578538
	US 1"		578540
WATTS RADIANT	US ¾"		578534
Watts RadiantPEX	US ½"		578536
	US ¾"		578538
	US 1"		578540
WATTS RADIANT	U 16 (¾")		578374
Watts RadiantPEX-AL	U 20 (¾")		578378
	U 25 (¾")		578380
	U 32 (1")		578382
Wavin Tigris K1/M1	U 14		578372
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
Wavin Tigris K5/M5	B 14		578466
	B 16		578468
	B 20		578472
	B 32		578476
	H 14		578398
	H 16		578400
	H 20		578406
	H 25		578408
	H 32		578412
	TH 14		578348
	TH 16		578352
	TH 20		578358
	TH 25		578360
	TH 32		578364
	TH 40		578624
	U 14		578372
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
	U 40		578386
	UP 14		578576
	UP 16		578578
	UP 20		578582
	UP 25		578584
	UP 32		578586
WeeConPress	M 12		578310
Alu	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
	V 12		578324
	V 15		578328
	V 18		578332
	V 22		578334
	V 28		578336
	V 35		578604
	V 12 45° (PR-2B)	Mini Z1	574502
	V 15 45° (PR-2B)	Mini Z1	574504
	V 18 45° (PR-2B)	Mini Z1	574506
	V 22 45° (PR-2B)	Mini Z1	574508
	V 28 45° (PR-2B)	Mini Z1	574510
	V 35 45° (PR-2B)	Mini Z1	574512
	SA 12		578510
	SA 15		578514
	SA 18		578518
	SA 22		578520
	SA 28		578522

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow. Observe the national regulations.

- ¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- ²⁾ For taking suitable pressing inserts.
- ³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website:

www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

REMS pressing tongs Mini

REMS pressing rings

Accessories for REMS radial presses 22 kN

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
WeeConPress C-Stahl	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
WeeConPress Inox	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
WeeConPress Kupfer	M 12		578310
	M 15		578312
	M 18		578314
	M 22		578316
	M 28		578318
	M 35		578390
	M 12 45° (PR-2B)	Mini Z1	574520
	M 15 45° (PR-2B)	Mini Z1	574522
	M 18 45° (PR-2B)	Mini Z1	574524
	M 22 45° (PR-2B)	Mini Z1	574526
	M 28 45° (PR-2B)	Mini Z1	574528
	M 35 45° (PR-2B)	Mini Z1	574530
WeeConFlex MVR	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	U 40		578386
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
WEM	U 16		578374
	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
WIELAND cuprotherm CTX	TH 26		578362
	TH 14		578348
	TH 16		578352
	TH 17		578354
	TH 20		578358
WKS-Press	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16		578352
	TH 20		578358
WÜRTH Würth	TH 26		578362
	HE 32		578370

System	Pressing tongs / pressing rings	Driven by adapter tongs	Art.-No.
X			
XtraConnect	F 16		578456
	F 20		578460
	F 26		578462
	F 32		578464
	F 16 45° (PR-2B)	Mini Z1	574550
	F 20 45° (PR-2B)	Mini Z1	574552
	F 26 45° (PR-2B)	Mini Z1	574554
	F 32 45° (PR-2B)	Mini Z1	574556
	H 16		578400
	H 20		578406
	H 26		578410
	H 32		578412
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 16		578374
	U 20		578378
	U 25		578380
	U 32		578382
(DN 26)	VP 16		578482
	VP 20		578484
	VP 32		578488
Z			
Zetaesse Multistrato EUROPEX	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
Zetaesse Multistrato ISOPEX	TH 14		578348
	TH 16		578352
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	U 14		578372
	U 16		578374
	U 18		578376
	U 20		578378
ZEWOTHERM Zewo Press Premium	TH 12		578346
	TH 16		578352
	TH 17		578354
	TH 18		578356
	TH 20		578358
	TH 26		578362
	TH 32		578364
	TH 40		578624
	TH 16		578352
	TH 20		578358
ZEWOTHERM Zewo Press PPSU	TH 26		578362
	TH 32		578364
	TH 16		578352
	TH 20		578358
	TH 26		578362
	TH 32		578364
	US ¾"		578534
	US ½"		578536
	US ¾"		578538
	US 1"		578540

Pressfitting systems for gas installations must only be pressed with REMS pressing tongs Mini/pressing rings which are highlighted in yellow.

Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For taking suitable pressing inserts.

³⁾ Only pressing tongs from designation "117" (1st quarter of 2017), "217" (2nd quarter of 2017) etc. can be used. The designation is stamped on every pressing jaw.

The suitability of REMS pressing tools for pressfitting systems: Date 14.10.2020. For the updated situation regarding suitability status check our website:

www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

See page 166 for adapter tongs. Pressing tongs for additional pressfitting systems on request.

Accessories

Description	Art.-No.	
Adapter tongs Mini Z1 for driving REMS pressing rings 45° (PR-2B)	578558	
Steel case with insert for adapter tongs Mini Z1 and adapter tongs Z1 and 6 REMS pressing rings V 12–35 45° (PR-2B) or M 12–35 45° (PR-2B) or F 16–32 45° (PR-2B)	574516	
Steel case with insert for 8 pressing tongs Mini/cropping tongs Mini and compartment for pipe cutter up to 42 mm	578295	
L-Boxx system case with inserts for 11 pressing tongs Mini and 6 pressing rings 45° (PR-2B)	578659	



REMS cropping tongs Mini

Accessories for REMS radial presses 22 kN

High performance cropping tongs Mini in forged and specially hardened steel for cutting threaded rods.

Steel, stainless steel up to
hardness classification 4.8 (400 N/mm²) M 6 – M 10

REMS cropping tongs Mini – cuts in just 2 seconds!

Made of forged and specially hardened steel.


Reversible cropping inserts for double service life.

M cropping inserts with high precision thread contour machined on CNC machining centres for exact guiding of the threaded rod in the cutting process. Pliers parts, cropping inserts and specially machined and hardened cutting edges, made to fit exactly, for cutting without burr.

Threaded rod can be screwed into a threaded connection of the pipe clip or the nut without rework after cutting.

Cutting device in pliers design (**Patent EP 1 459 825, patent US 7,284,330**). Very compact design and low weight of the REMS Mini cropping tongs due to special arrangement of the cropping tongs connection (**Patent EP 1 952 948**). Recesses in the connecting plate for safe guidance of the connecting lugs for offset-free pressing (**Patent EP 2 347 862**).

Can be driven by all REMS radial presses 22 kN.



German Quality Product



Patent EP 1 952 948
Patent EP 1 459 825
Patent US 7,284,330
Patent EP 2 347 862

Supply format

REMS cropping tongs Mini. Cropping tongs with 1 pair of reversible cropping inserts for steel, stainless steel, M 6 – M 10. In a carton.

Description	for threaded rods	Art.-No.	
REMS cropping tongs Mini M 6	M 6	578620	
REMS cropping tongs Mini M 8	M 8	578621	
REMS cropping tongs Mini M 10	M 10	578622	

Accessories

Description	for threaded rods	Art.-No.	
Cropping inserts M 6 (pair)	M 6	571891	
Cropping inserts M 8 (pair)	M 8	571896	
Cropping inserts M 10 (pair)	M 10	571866	
Steel case with insert for 8 pressing tongs Mini/cropping tongs Mini and compartment for pipe cutter up to 42 mm		578295	

