

The Flexcon connection group 1/2" is used for draining and/or filling the system and disconnecting an expansion vessel in heating and cooling installations.

Technical Specifications

- Minimum/Maximum system temperature: -10 °C / 120 °C.
- System pressure: 0 - 6 bar.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- The set consists of a sealed ball valve including an integrated filling and drain ball valve and pressure gauge.



Description		Flexcon Connection group 1/2" (K15)
Order Code		27290
GTIN		08712874272903
Model		<u>Flexcon Connection Group 1/2</u>
Connection	A	R 1/2" / K15 *
	B	R 1/2" / K15 *
	C	3/4"
With pressure gauge		yes

* Compression connection.

Classification General Data

Etim Group	Measuring and control devices
Etim Class	Expansion tank connection group
Product Name	Flexcon Connection group 1/2" (K15)
Brand	Flamco
Product Type	1/2
Artikelnummer	27290

Attributes

Material	Brass
Nominal diameter	1/2 inch (15)
Outer pipe diameter connection 1	15.2 Millimetre
Connection 1	Compression ring
Outer pipe diameter connection 2	15.2 Millimetre
Connection 2	Compression ring
With pressure gauge	Yes
Sealable	No
With filling/drain tap	Yes
Right-angled model	Yes

Find more information online:

[Installation and operating instruction](#)
[Flexcon Connection Group 1/2 RFA](#)
[Export catalogue](#)
[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com