

This insulation set for Flamcovent Clean (Smart) can be easily attached and consists of two halves that lock into each other by means of hook fasteners and deep-drawn synthetic caps. The melamine insulation foam (thickness 50 mm) is glued to the polystyrene outer jacket (thickness 1 mm).





### Advantages


- Suitable for retrospective installation.
- 100% recyclable.

### Technical Specifications

- $\lambda$ -value: 0.035 W/mK.
- Fire class B2 according to DIN 4102.
- Colour: aluminium coloured (RAL 9006).



Type	Dimensions		Weight [kg]		Order Code
	A [mm]	B [mm]			
Flamcovent Clean IsoPlus 50	502	280	1.4	1	28860
Flamcovent Clean IsoPlus 65	502	280	1.5	1	28861
Flamcovent Clean IsoPlus 80	694	380	2.3	1	28862
Flamcovent Clean IsoPlus 100	694	380	2.4	1	28863

Type	Dimensions		Weight [kg]	 -	Order Code
	A [mm]	B [mm]			
Flamcovent Clean IsoPlus 125	866	470	3.5	1	28864
Flamcovent Clean IsoPlus 150	866	470	3.6	1	28865
Flamcovent Clean IsoPlus 200	1178	560	5.5	1	28866

**Find more information online:**

[Installation and operating instruction](#)

[Export catalogue](#)

[Packaging data](#)

Fort Blauwkapel 1  
1358 DB, Almere - nl

T +31 (0)36 52 62 300  
E [info@aalberts-hfc.com](mailto:info@aalberts-hfc.com)  
I [flamcogroup.com](http://flamcogroup.com)