

This insulation set for Flamco Clean (Smart) can be easily attached and consists of two halves that lock into each other by means of hook fasteners and deep-drawn synthetic caps. The melamine insulation foam (thickness 50 mm) is glued to the polystyrene outer jacket (thickness 1 mm).




Advantages

- Suitable for retrospective installation.
- 100% recyclable.

Technical Specifications

- Insulation value (λ): 0.035 W/mK.
- Fire class B2 according to DIN 4102.
- Colour: aluminium coloured (RAL 9006).



Type	Dimensions		Weight [kg]		Order Code
	A [mm]	B [mm]			
Flamco Clean IsoPlus 50	460	280	1.3	1	28870
Flamco Clean IsoPlus 65	460	280	1.4	1	28871
Flamco Clean IsoPlus 80	615	380	2.2	1	28872
Flamco Clean IsoPlus 100	615	380	2.3	1	28873

Type	Dimensions		Weight [kg]	 -	Order Code
	A [mm]	B [mm]			
Flamco Clean IsoPlus 125	755	470	3.5	1	28874
Flamco Clean IsoPlus 150	755	470	3.5	1	28875
Flamco Clean IsoPlus 200	965	560	5.0	1	28876

Find more information online:
[Installation and operating instruction](#)
[Export catalogue](#)
[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com