

This insulation set for Flamcovent (Smart) can be easily attached and consists of two halves that lock into each other by means of hook fasteners and deep-drawn synthetic caps. The melamine insulation foam (thickness 50 mm) is glued to the polystyrene outer jacket (thickness 1 mm).




Advantages

- Suitable for retrospective installation.
- 100% recyclable.

Technical Specifications

- Insulation value (λ): 0.035 W/mK.
- Fire class B2 according to DIN 4102.
- Colour: aluminium coloured (RAL 9006).



Type	Dimensions		Weight [kg]		Order Code
	A [mm]	B [mm]			
Flamcovent IsoPlus 50	500	280	1.3	1	28160
Flamcovent IsoPlus 65	500	280	1.4	1	28161
Flamcovent IsoPlus 80	650	380	2.2	1	28162
Flamcovent IsoPlus 100	650	380	2.3	1	28163

Type	Dimensions		Weight [kg]	 -	Order Code
	A [mm]	B [mm]			
Flamcovent IsoPlus 125	790	470	3.4	1	28164
Flamcovent IsoPlus 150	790	470	3.5	1	28165
Flamcovent IsoPlus 200	1000	560	5.0	1	28166

Find more information online:
[Installation and operating instruction](#)
[Flamcovent IsoPlus RFA](#)
[Export catalogue](#)
[Packaging data](#)

Fort Blauwkapel 1
 1358 DB, Almere - nl

T +31 (0)36 52 62 300
 E info@aalberts-hfc.com
 I flamcogroup.com