

Suitable for use in potable water installations where ACS applies.

To be installed at places where the air collects. Float operated, collected air in the Flexvent causing the float to drop and open the air release valve.

### Technical Specifications

- Minimum/Maximum working temperature: 0 °C / 120 °C.
- Minimum/Maximum working pressure: 0.2 / 10.0 bar.



### Classification General Data

|               |                               |
|---------------|-------------------------------|
| Etim Group    | Measuring and control devices |
| Etim Class    | De-aerator (automatic)        |
| Product Name  | Flexvent Top Aqua Rp1/2"      |
| Brand         | FLAMCO                        |
| Product Type  | Flexvent                      |
| Artikelnummer | 28508                         |
| GTIN          | 08712874285088                |

### Attributes

|                                      |                                                            |
|--------------------------------------|------------------------------------------------------------|
| Housing material                     | Brass                                                      |
| Material valve                       | Other                                                      |
| Material float                       | Other                                                      |
| Nominal diameter                     | DN 15                                                      |
| Outer pipe diameter                  | 21.3 Millimetre                                            |
| Connection 1                         | Internal thread cylindrical BSPT-Rp (ISO 7-1 / EN 10226-1) |
| Max. operating pressure at 20 °C     | 10 Bar                                                     |
| Max. medium temperature (continuous) | 120 Degrees celsius                                        |
| Surface protection                   | Untreated                                                  |
| Length of connection 1               | 12.4 Millimetre                                            |
| Height                               | 87 Millimetre                                              |
| Lockable                             | No                                                         |
| With leakage protection              | No                                                         |

### Find more information online:

[Installation and operating instruction](#)

[Certificate ACS](#)

[Statement of Conformity](#)

[PZH certificate](#)

[Flexvent Top Aqua DWG](#)

[Flexvent Top Aqua STEP](#)

[Flexvent Top Aqua RFA](#)

[Folder](#)

[Flexvent Life Cycle Assessment](#)

[Leaflet](#)

[Export catalogue](#)

[Packaging data](#)

Fort Blauwkapel 1  
1358 DB, Almere - nl

T +31 (0)36 52 62 300  
E [info@aalberts-hfc.com](mailto:info@aalberts-hfc.com)  
I [flamcogroup.com](http://flamcogroup.com)