





Technical Specifications

- Model: Red brass
- Permissible operating pressure: PB 10 bar
- Max. operating temperature: TB 90 °C
- Flow medium: Domestic water



Type	Connection	Nominal width	Range of setting temperature [°C]	Installed length of valve [mm]	Dimension insulation [mm]				Order Code
					A	B	C		
NexusValve TW (F) DN15 with insulation and thermometer	Rp 1/2"	DN 15	50-60	98	143	162	82	10	M1206320
NexusValve TW (F) DN15 with insulation and thermometer	Rp 1/2"	DN 15	30-50	98	143	162	82	10	M1206310
NexusValve TW (F) DN20 with insulation and thermometer	Rp 3/4"	DN 20	30-50	125	143	162	90	10	M1206350

Type	Connection	Nominal width	Range of setting temperature [°C]	Installed length of valve [mm]	Dimension insulation [mm]				Order Code
					A	B	C	-	
NexusValve TW (F) DN20 with insulation and thermometer	Rp 3/4"	DN 20	50-60	125	143	162	90	10	M1206360
NexusValve TW (F) DN25 with insulation and thermometer	Rp 1"	DN 25	50-60	136	157	162	110	5	M1206400



Find more information online:
[Installation and operating instruction](#)
[Certificate DVGW](#)
[Certificate ASC](#)
[Certificate RUS](#)
[Technical brochure](#)
[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl


T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com

For metal pipe threaded joints.




Technical Specifications

- Model: Red brass
- Permissible operating pressure: PB 10 bar
- Max. operating temperature: TB 90 °C
- Flow medium: Domestic water



Type	Connection	Nominal width	Range of setting temperature [°C]	Installed length of valve [mm]	Dimension insulation [mm]				Order Code
					A	B	C		
NexusValve TW (M) DN15 with insulation and thermometer	G 3/4" M	DN 15	50-60	98	143	162	82	10	M1206340
NexusValve TW (M) DN20 with insulation and thermometer	G 1" M	DN 20	50-60	103	143	162	90	10	M1206380
NexusValve TW (M) DN25 with insulation and thermometer	G 1 1/2" M	DN 25	50-60	113	157	162	110	5	M1206420



Find more information online:

[Installation and operating instruction](#)

[Certificate DVGW](#)

[Certificate ASC](#)

[Certificate RUS](#)

[Technical brochure](#)

[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl


T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com



Technical Specifications

- Model: Red brass
- Permissible operating pressure: PB 10 bar
- Max. operating temperature: TB 90 °C
- Flow medium: Domestic water

Type	Conne ction	Nomin al width	Range of setting tempe rature [°C]	Install ed length of valve [mm]		Order Code
NexusValve TW (F) DN15	Rp 1/2"	DN 15	50-60	98	10	M1206325
NexusValve TW (F) DN20	Rp 3/4"	DN 20	50-60	125	10	M1206365
NexusValve TW (F) DN25	Rp 1"	DN 25	50-60	136	5	M1206405





flamco

NexusValve TW - Domestic water circulation valves female thread

Product Data Sheet 2025/02/10

Find more information online:

[Installation and operating instruction](#)

[Certificate DVGW](#)

[Certificate ASC](#)

[Certificate RUS](#)

[Technical brochure](#)

[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com


For metal pipe threaded joints.



Technical Specifications

- Model: Red brass
- Permissible operating pressure: PB 10 bar
- Max. operating temperature: TB 90 °C
- Flow medium: Domestic water

Type	Conne ction	Nomin al width	Range of setting tempe rature [°C]	Install ed length of valve [mm]		Order Code
NexusValve TW (M) DN15	G 3/4" M	DN 15	50-60	98	10	M1206345
NexusValve TW (M) DN20	G 1" M	DN 20	50-60	103	10	M1206385



Find more information online:[Installation and operating instruction](#)[Certificate DVGW](#)[Certificate ASC](#)[Certificate RUS](#)[NexusValve TW RFA](#)[NexusValve TW DWG](#)[NexusValve TW STEP](#)[Technical brochure](#)[Packaging data](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamcogroup.com