

## Product Data Sheet

### Flexcon VSV - 6.0 bar

**Vessels to protect Flexcon expansion vessels on elevated temperature systems.**

The vessels are fitted in between the expansion vessel and the system return.

System water flows from the installation into the top of the vessel. From the bottom of the vessel, significantly cooler water is fed into the expansion vessel.



Type	Capacity [l]	Dimensions		Connection to		Weight [kg]	###	Order Code
		Ø [mm]	H. [mm]	Vessel	System			
<b>Flexcon VSV 100</b>	100	484	794	Rp 1 1/2"	Rp 1 1/2"	26.5	1	23386
<b>Flexcon VSV 200</b>	200	484	1304	Rp 1 1/2"	Rp 1 1/2"	28.8	1	23380
<b>Flexcon VSV 350</b>	350	484	2124	Rp 1 1/2"	Rp 1 1/2"	55.0	1	23381
<b>Flexcon VSV 500</b>	500	600	2025	Rp 2"	Rp 2"	64.0	1	23382
<b>Flexcon VSV 750</b>	750	790	1904	Rp 2"	Rp 2"	96.0	1	23383
<b>Flexcon VSV 1000</b>	1000	790	2255	Rp 2"	Rp 2"	114.0	1	23384



### Technical information

- Maximum working pressure: 6.0 bar.
- Maximum working temperature: 110 °C.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- This vessel is manufactured in accordance with sound engineering practice and satisfies the essential design requirements of the member state.
- Red (RAL 3002) epoxy powder coating.