

Product Data Sheet

BRS Clips - Stainless Steel

Stainless steel universal clips for mounting stainless steel pipes to the wall or ceiling.

For use in situations where stainless steel mounting material is desired or required, such as food processing, facilities, laboratories, the chemical industry, etc.



Type	Ø Pipe		Connection	Strip dimensions [mm]	Max. working load [N]	Dimensions			###	Order Code
	Nom. ["]	Ext. dia. [mm]				A [mm]	B [mm]	C [mm]		
BRS 8 - 10 SST	1/8"	8 - 10	M 8/10	20 x 1.5	1000	43	7	16	50	38475
BRS 12 - 14 SST	1/4"	12 - 14	M 8/10	20 x 1.5	1000	49	9	16	50	38476
BRS 15 - 19 SST	3/8"	15 - 19	M 8/10	20 x 1.5	1000	50	11	16	50	38477
BRS 20 - 25 SST	1/2"	20 - 25	M 8/10	20 x 1.5	1000	60	16	16	50	38478
BRS 26 - 30 SST	3/4"	26 - 30	M 8/10	20 x 1.5	1000	64	19	16	50	38479
BRS 32 - 36 SST	1"	32 - 36	M 8/10	20 x 1.5	1000	71	22	16	50	38480
BRS 38 - 43 SST	1 1/4"	38 - 43	M 8/10	20 x 1.5	1000	79	25	16	50	38481
BRS 44 - 49 SST	1 1/2"	44 - 49	M 8/10	20 x 1.5	1000	84	28	16	50	38482
BRS 50 - 55 SST		50 - 55	M 8/10	20 x 1.5	1000	91	29	16	50	38483
BRS 56 - 61 SST	2"	56 - 61	M 8/10	20 x 1.5	1000	93	34	16	50	38484
BRS 62 - 67 SST		62 - 67	M 8/10	20 x 2.0	1000	109	36	16	50	38485
BRS 68 - 73 SST		68 - 73	M 8/10	20 x 2.0	1300	115	39	16	50	38486
BRS 75 - 80 SST	2 1/2"	75 - 80	M 8/10	20 x 2.0	1300	118	44	16	50	38487
BRS 82 - 86 SST		82 - 86	M 8/10	20 x 2.0	1300	124	45	16	50	38488
BRS 87 - 92 SST	3"	87 - 92	M 8/10	20 x 2.0	1300	129	50	16	50	38489

Type	Ø Pipe		Connection	Strip dimensions [mm]	Max. working load [N]	Dimensions			###	Order Code
	Nom. ["]	Ext. dia. [mm]				A [mm]	B [mm]	C [mm]		
BRS 95 - 102 SST	3 1/2"	95 - 102	M 8/10	20 x 2.5	2150	146	54	16	50	38490
BRS 108 - 116 SST	4"	108 - 116	M 8/10	20 x 2.5	2150	160	62	16	25	38491
BRS 121 - 127 SST		121 - 127	M 8/10	20 x 2.5	2150	176	66	16	25	38492
BRS 131 - 141 SST	5"	131 - 141	M 8/10	20 x 2.5	2150	188	75	16	25	38493
BRS 159 - 163 SST		159 - 163	M 8/10	20 x 2.5	2150	211	84	16	25	38494
BRS 165 - 169 SST	6"	165 - 169	M 8/10	20 x 2.5	2150	220	89	16	25	38495
BRS 192 - 202 SST		192 - 202	M 8/10	20 x 3.0	2150	252	104	16	25	38496
BRS 210 - 220 SST	8"	210 - 220	M 8/10	20 x 3.0	2150	270	113	16	25	38497

Advantages

- Suitable for short-distance mounting.

Technical information

- Stainless steel AISI 316 (1.4401 according to EN 10088).
- Safety margin for minimal breaking load (V) = 3.
- Connection: M 8/10.

Find more information online:

[CAD drawings](#)

[Extra documentation](#)